

屋内照明器具特性

品番（品名）NNLK42762J+NNL4300EDT

光源LED6500_85_2880 ×1 2880.0 lm

管理番号K0132392（1）DB1

BZ分類BZ4

器具効率			100 %		反射率	天井	80 %				70 %				50 %				30 %				0 %	
						壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
						床	10 %				10 %				10 %				10 %				0 %	
						室指数	照明率 (X0.01)																	
保守率			良 中 否 0.81 0.77 0.68		0.6	59	47	40	35	58	47	40	35	55	46	39	34	53	45	39	34	32		
					0.8	70	59	51	46	68	58	51	46	66	57	50	46	63	55	50	45	43		
					1.0	76	66	59	54	75	66	59	54	72	64	58	54	70	63	57	53	51		
					1.25	82	73	67	62	81	73	66	61	78	71	65	61	75	69	64	60	58		
下方投影面積			cm ²		1.5	86	78	72	67	85	77	71	67	82	75	70	66	79	74	69	66	63		
					2.0	91	85	80	75	90	84	79	75	87	82	78	74	84	80	76	73	71		
等価発光面積			cm ²		2.5	95	89	84	80	93	88	84	80	90	86	82	79	88	84	81	78	76		
					3.0	97	92	88	84	95	91	87	84	93	89	86	83	90	87	84	82	79		
5m			2.03 m		2.18 m		4.0	100	96	92	89	98	95	92	89	95	93	90	87	93	91	88	86	84
							5.0	101	98	95	93	100	97	94	92	97	95	93	91	95	93	91	89	86
5			3.33		3.34		7.0	103	101	99	97	102	100	98	96	99	98	96	94	97	95	94	93	90
							10.0	105	103	101	100	103	102	100	99	101	100	98	97	99	97	96	95	93
			3.98		3.94		10.0	105	103	101	100	103	102	100	99	101	100	98	97	99	97	96	95	93

配光曲線

ランタ光束1000 lm

—— 管軸に垂直（A）
 ---- 管軸に平行（B）

直射水平面照度

ランタ光束1000 lm

