

屋内照明器具特性	
品番 (品名)	NNN1 1 1 1 1
光源	LDA5 L - D - G - E17 / S / Z4 ×1 440.0 l m
管理番号	K0173114 (0) DB1
BZ分類	BZ9 / 0.7 / BZ8

器具効率		53 %	反射率	天井	80 %				70 %				50 %				30 %				0 %			
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %			
				床	10 %				10 %				10 %				10 %				0 %			
上方光束		25 %	室指数	照明率 (X0.01)																			Z C M	
下方光束		28 %																						
保守率		良 中 否	0.69	0.6	24	17	13	10	22	16	12	9	18	13	10	8	15	11	8	6	4			
			0.67	0.8	28	22	17	14	26	20	16	13	22	17	14	11	18	14	11	9	6			
			0.63	1.0	31	25	21	17	29	23	19	16	24	20	16	14	20	16	14	11	7			
				1.25	34	28	24	21	32	26	22	19	26	22	19	17	22	18	16	14	9			
下方投影面積		c m ²	1.5	37	31	27	23	34	29	25	22	28	24	21	19	23	20	18	16	11				
等価発光面積			c m ²	2.0	40	35	31	28	36	32	29	26	31	27	25	22	25	23	21	19	13			
取付 高さ	器具間隔最大限		2.5	41	37	34	31	38	35	31	29	32	29	27	25	27	25	23	21	15				
	横方向 (A)		縦方向 (B)	3.0	43	39	36	33	40	36	33	31	34	31	29	27	28	26	24	22	16			
H m	1.79 H m	1.70 H m	4.0	45	42	39	36	41	39	36	34	35	33	31	29	30	28	26	25	18				
			5.0	46	43	41	39	43	40	38	36	36	35	33	31	31	29	28	26	19				
			7.0	47	45	43	42	44	42	40	39	38	36	35	34	32	31	30	29	21				
			10.0	49	47	45	44	45	44	42	41	39	38	37	36	33	32	31	30	23				

