

屋内照明器具特性	
品番 (品名)	NNN17513K+NNN89991
光源	LED3000_80_4950 ×1 4950.0 lm
管理番号	K0150640 (0) DB 1
BZ分類	BZ1/1.1/BZ2/2.8/BZ3/6.0/BZ4

器具効率		1 0 0 %	反射率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %
上方光束		2 0 %		床	1 0 %				1 0 %				1 0 %				1 0 %				0 %
下方光束		8 0 %		室指数	照明率 (X 0 . 0 1) Z C M																
保守率		良 中 否	0 . 7 6	0 . 6	7 0	6 2	5 7	5 3	6 8	6 1	5 6	5 2	6 4	5 8	5 4	5 1	6 1	5 6	5 2	5 0	4 7
			0 . 7 2	0 . 8	7 6	6 8	6 3	5 9	7 4	6 7	6 2	5 8	7 0	6 4	6 0	5 7	6 6	6 1	5 8	5 5	5 2
			1 . 0	8 0	7 3	6 8	6 4	7 8	7 1	6 7	6 3	7 3	6 8	6 4	6 1	6 9	6 5	6 1	5 9	5 5	
			0 . 6 4	1 . 2 5	8 4	7 7	7 2	6 8	8 1	7 5	7 1	6 7	7 6	7 2	6 8	6 5	7 2	6 8	6 5	6 2	5 8
下方投影面積		c m ²	1 . 5	8 7	8 1	7 6	7 2	8 4	7 8	7 4	7 0	7 9	7 4	7 1	6 8	7 4	7 0	6 7	6 5	6 0	
等価発光面積			c m ²	2 . 0	9 0	8 5	8 1	7 7	8 7	8 3	7 9	7 5	8 2	7 8	7 5	7 2	7 6	7 3	7 1	6 9	6 3
取付 高さ	器具間隔最大限		2 . 5	9 3	8 8	8 4	8 1	9 0	8 5	8 2	7 9	8 4	8 0	7 7	7 5	7 8	7 6	7 3	7 1	6 5	
	横方向 (A) 縦方向 (B)		3 . 0	9 4	9 0	8 7	8 3	9 1	8 7	8 4	8 1	8 5	8 2	8 0	7 7	7 9	7 7	7 5	7 3	6 7	
H m	0 . 9 8 H m	0 . 9 7 H m	4 . 0	9 6	9 3	9 0	8 7	9 3	9 0	8 7	8 5	8 7	8 5	8 2	8 0	8 1	7 9	7 8	7 6	6 9	
			5 . 0	9 8	9 5	9 2	9 0	9 4	9 2	8 9	8 7	8 8	8 6	8 4	8 3	8 2	8 1	7 9	7 8	7 1	
			7 . 0	9 9	9 7	9 5	9 3	9 6	9 4	9 2	9 0	9 0	8 8	8 7	8 5	8 4	8 2	8 1	8 0	7 3	
			1 0 . 0	1 0 0	9 9	9 7	9 6	9 7	9 6	9 4	9 3	9 1	9 0	8 9	8 7	8 5	8 4	8 3	8 2	7 4	

