

屋内照明器具特性	
品番 (品名)	NNN2 1 8 5 5 W
光源	LED5000_70_60 x1 60.0 l m
管理番号	K0170758 (0) DB 1
B Z 分類	BZ2

器具効率		1 0 0 %	反射率	天井	8 0 %					7 0 %				5 0 %				3 0 %				0 %	
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %		
				床	1 0 %					1 0 %				1 0 %				1 0 %				0 %	
上方光束		0 %	室指数	照明率 (X 0 . 0 1)																			Z C M
下方光束				1 0 0 %																			
保守率		良 中 否	0 . 6 7	0 . 6	6 9	6 0	5 3	4 9	6 8	5 9	5 3	4 9	6 6	5 8	5 3	4 9	6 4	5 7	5 3	4 9	4 7		
			0 . 6 3	0 . 8	7 8	7 0	6 4	6 0	7 7	6 9	6 4	6 0	7 5	6 8	6 3	6 0	7 3	6 7	6 3	6 0	5 8		
			0 . 5 6	1 . 0	8 4	7 7	7 1	6 7	8 3	7 6	7 1	6 7	8 1	7 5	7 0	6 7	7 9	7 4	7 0	6 7	6 5		
				1 . 2 5	8 9	8 3	7 8	7 4	8 8	8 2	7 7	7 4	8 6	8 0	7 6	7 3	8 4	7 9	7 6	7 3	7 1		
下方投影面積		c m ²	1 . 5	9 2	8 6	8 2	7 8	9 1	8 6	8 1	7 8	8 9	8 4	8 0	7 7	8 7	8 3	7 9	7 7	7 5			
等価発光面積			c m ²	2 . 0	9 6	9 2	8 8	8 4	9 5	9 1	8 7	8 4	9 3	8 9	8 6	8 3	9 0	8 7	8 5	8 2	8 0		
取付 高さ	器具間隔最大限		2 . 5	9 9	9 5	9 1	8 9	9 7	9 4	9 1	8 8	9 5	9 2	8 9	8 7	9 3	9 0	8 8	8 6	8 4			
	横方向 (A)		縦方向 (B)	3 . 0	1 0 0	9 7	9 4	9 1	9 9	9 6	9 3	9 1	9 7	9 4	9 2	9 0	9 4	9 2	9 0	8 9	8 6		
H m	1 . 1 5 H m	1 . 1 5 H m	4 . 0	1 0 2	1 0 0	9 7	9 5	1 0 1	9 9	9 6	9 4	9 9	9 7	9 5	9 3	9 7	9 5	9 3	9 2	8 9			
			5 . 0	1 0 4	1 0 1	9 9	9 8	1 0 2	1 0 0	9 8	9 7	1 0 0	9 8	9 7	9 5	9 8	9 6	9 5	9 4	9 1			
			7 . 0	1 0 5	1 0 3	1 0 2	1 0 0	1 0 4	1 0 2	1 0 1	1 0 0	1 0 1	1 0 0	9 9	9 8	9 9	9 8	9 7	9 6	9 4			
			1 0 . 0	1 0 6	1 0 5	1 0 4	1 0 3	1 0 5	1 0 4	1 0 3	1 0 2	1 0 2	1 0 2	1 0 1	1 0 0	1 0 0	9 9	9 9	9 8	9 5			

