

屋内照明器具特性	
品番 (品名)	NNN5 4 5 4 0 B
光源	NNU140105LE9 ×1 1130.0 lm
管理番号	K0147997 (*) DB 1
B Z 分類	BZ2

器具効率		86 %	反射率	天井	80 %				70 %				50 %				30 %				0 %			
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %			
				床	10 %				10 %				10 %				10 %				0 %			
上方光束		0 %	室指数	照明率 (X0.01)																			Z	CM
下方光束		86 %																						
保守率		良 中 否	0.83	0.6	60	52	47	44	59	52	47	44	58	51	47	43	56	50	46	43	42			
			0.81	0.8	68	61	56	52	67	60	56	52	65	59	55	52	63	58	55	52	51			
			0.77	1.0	73	66	62	58	72	66	61	58	70	65	61	58	68	64	60	58	56			
				1.25	77	71	67	64	76	70	66	63	74	69	66	63	72	68	65	63	61			
下方投影面積		cm ²	1.5	79	74	70	67	78	74	70	67	76	72	69	66	74	71	68	66	64				
等価発光面積		cm ²	2.0	83	79	75	72	82	78	75	72	79	76	74	71	78	75	73	71	69				
取付 高さ	器具間隔最大限		2.5	85	81	78	76	84	80	78	75	82	79	77	75	80	77	75	74	72				
	横方向 (A)		縦方向 (B)	3.0	86	83	81	78	85	82	80	78	83	81	79	77	81	79	77	76	74			
H m	1.15 H m	1.15 H m	4.0	88	85	83	82	87	85	83	81	85	83	81	80	83	81	80	79	77				
			5.0	89	87	85	84	88	86	84	83	86	84	83	82	84	83	82	81	78				
			7.0	90	89	87	86	89	88	86	85	87	86	85	84	85	84	83	83	80				
			10.0	91	90	89	88	90	89	88	87	88	87	86	86	86	85	85	84	82				

