

屋内照明器具特性	
品番 (品名)	NNN5 4 5 4 0 W
光源	NNU141105LE9 ×1 1110.0 lm
管理番号	K0147995 (0) DB 1
B Z 分類	BZ2

器具効率		81 %	反射率	天井	80 %				70 %				50 %				30 %				0 %	
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
					床	10 %				10 %				10 %				10 %				0 %
						照明率 (X0.01) ZCM																
保守率		良 中 否	0.83	0.6	58	51	46	43	57	50	46	43	56	49	45	43	54	49	45	42	41	
			0.81	0.8	65	58	54	50	64	58	53	50	62	57	53	50	61	56	53	50	49	
			0.77	1.0	69	63	59	56	68	63	59	56	66	62	58	55	65	61	57	55	54	
				1.25	73	68	64	61	72	67	63	60	70	66	63	60	68	65	62	60	58	
下方投影面積 等価発光面積		cm ² cm ²		1.5	75	71	67	64	74	70	66	64	72	69	66	63	71	67	65	63	61	
				2.0	78	75	71	69	77	74	71	68	75	72	70	68	74	71	69	67	65	
				2.5	80	77	74	72	79	76	74	72	77	75	73	71	76	73	72	70	68	
				3.0	82	79	76	74	81	78	76	74	79	77	75	73	77	75	73	72	70	
H m	0.76 H m		0.76 H m	4.0	83	81	79	77	82	80	78	77	80	79	77	76	78	77	76	75	73	
				5.0	84	82	81	79	83	82	80	79	81	80	79	78	79	78	77	76	74	
				7.0	85	84	83	82	84	83	82	81	82	81	80	80	81	80	79	78	76	
				10.0	86	85	84	83	85	84	83	83	83	83	82	81	81	81	80	80	78	

