

屋内照明器具特性	
品番 (品名)	NNN57004+NEL4500HW
光源	LED4000_85_7380 ×1 7380.0 lm
管理番号	K0193070 (0) DB1
BZ分類	BZ5

器具効率		100 %	反射率	天井	80 %				70 %				50 %				30 %				0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
				室指数	照明率 (X0.01) ZCM																
保守率		良 中 否	0.77	0.6	55	43	35	30	53	42	34	29	49	40	33	28	46	38	32	28	25
			0.72	0.8	64	53	45	39	62	51	44	39	58	49	42	37	54	46	41	36	33
			0.68	1.0	71	60	52	46	68	58	51	46	63	55	49	44	59	52	47	42	39
				1.25	76	66	59	53	74	65	58	52	69	61	55	50	64	58	53	49	44
下方投影面積		cm ²		1.5	80	71	64	59	77	69	63	57	72	65	60	55	67	62	57	53	49
			等価発光面積	cm ²	2.0	86	78	72	66	83	76	70	65	77	72	67	63	72	68	64	60
取付 高さ	器具間隔最大限			2.5	89	82	77	72	86	80	75	71	81	76	71	68	76	72	68	65	60
	横方向 (A) 縦方向 (B)			3.0	91	86	81	76	89	83	79	75	83	79	75	71	78	74	71	68	63
1.5m	1.89 m	2.1 m	4.0	95	90	86	82	92	87	84	80	86	83	79	77	81	78	76	73	67	
2	2.48	2.6	5.0	97	93	89	86	94	90	87	84	88	85	82	80	83	81	78	76	70	
2.5	3.08	3.14	7.0	99	96	93	90	96	93	91	88	91	88	86	84	85	84	82	80	74	
3	3.68	3.69	10.0	101	98	96	94	98	96	94	92	92	91	89	88	87	86	85	83	77	

