

# 屋内照明器具特性

品番 (品名)	NYY75074 + NTS90150	
光源	LED4000_70_1005 ×1	1005.0 lm
管理番号	K0152451 (8) DJ 1	
BZ分類	BZ1	

器具効率	101%	天井	80%				70%				50%				30%				0%	
	上方光束 0%		反射率	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
下方光束	101%	床		10%				10%				10%				10%				0%
室指数	照明率 ( X0.01 )																			ZCM
保守率	良 0.67	0.6	0.6	89	85	81	79	89	84	81	79	88	84	81	79	87	83	81	79	78
	中 0.63		0.8	94	90	87	85	94	90	87	85	92	89	86	85	91	88	86	84	83
	否 0.56		1.0	97	94	91	89	97	93	90	88	95	92	90	88	94	91	89	88	87
下方投影面積 等価発光面積	cm <sup>2</sup>	cm <sup>2</sup>	1.25	100	96	94	92	99	96	93	92	97	95	93	91	96	94	92	91	89
			1.5	101	98	96	94	100	98	95	94	99	96	95	93	97	95	94	92	91
			2.0	103	101	99	97	102	100	98	97	101	99	97	96	99	97	96	95	93
取付高さ	器具間隔最大限		2.5	104	102	101	99	103	102	100	99	102	100	99	98	100	99	97	96	95
	横方向 (A)	縦方向 (B)	3.0	105	103	102	100	104	103	101	100	102	101	100	99	100	99	98	98	96
Hm	0.50Hm	0.50Hm	4.0	106	105	104	102	105	104	103	102	103	102	101	100	101	100	100	99	97
			5.0	107	106	105	104	106	105	104	103	104	103	102	101	102	101	100	100	97
			7.0	107	107	106	105	106	106	105	104	104	104	103	102	102	102	101	101	98
			10.0	108	107	107	106	107	106	106	105	105	104	104	103	103	102	102	102	99

