

屋内照明器具特性	
品番 (品名)	NNQ35013Z
光源	LED3000_70_8222.7 ×1 8222.7 l m
管理番号	K0169881 (0) DR 1
B Z 分類	BZ4 / 1.4 / BZ3

器具効率		1 0 0 %	反射率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %			
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %			
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %			
上方光束		0 %	室指数	照明率 (X 0 . 0 1)																			Z C M	
下方光束				1 0 0 %																				
保守率		良 中 否	0 . 6 7	0 . 6	6 0	4 9	4 2	3 6	5 9	4 8	4 1	3 6	5 7	4 7	4 1	3 6	5 5	4 6	4 0	3 6	3 4			
			0 . 6 3	0 . 8	7 0	6 0	5 3	4 8	6 9	5 9	5 2	4 7	6 7	5 8	5 2	4 7	6 4	5 7	5 1	4 7	4 5			
			0 . 5 6	1 . 0	7 7	6 8	6 1	5 5	7 6	6 7	6 0	5 5	7 3	6 5	5 9	5 5	7 1	6 4	5 9	5 5	5 3			
				1 . 2 5	8 3	7 5	6 8	6 3	8 2	7 4	6 8	6 3	7 9	7 2	6 7	6 2	7 6	7 0	6 6	6 2	6 0			
下方投影面積 等価発光面積		c m ² c m ²	1 . 5	8 7	7 9	7 3	6 9	8 6	7 8	7 3	6 8	8 3	7 7	7 2	6 8	8 0	7 5	7 1	6 7	6 5				
			2 . 0	9 2	8 6	8 1	7 7	9 1	8 5	8 0	7 6	8 8	8 3	7 9	7 5	8 5	8 1	7 8	7 5	7 2				
			2 . 5	9 5	9 0	8 6	8 2	9 4	8 9	8 5	8 2	9 1	8 7	8 4	8 1	8 9	8 5	8 2	8 0	7 7				
取付 高さ	器具間隔最大限		3 . 0	9 8	9 3	8 9	8 6	9 6	9 2	8 8	8 5	9 4	9 0	8 7	8 4	9 1	8 8	8 5	8 3	8 1				
	横方向 (A)	縦方向 (B)	4 . 0	1 0 0	9 7	9 4	9 1	9 9	9 6	9 3	9 0	9 6	9 4	9 1	8 9	9 4	9 2	9 0	8 8	8 5				
H m	1 . 1 9 H m	1 . 1 9 H m	5 . 0	1 0 2	9 9	9 6	9 4	1 0 1	9 8	9 6	9 3	9 8	9 6	9 4	9 2	9 6	9 4	9 2	9 0	8 8				
			7 . 0	1 0 4	1 0 2	1 0 0	9 8	1 0 2	1 0 1	9 9	9 7	1 0 0	9 8	9 7	9 5	9 8	9 6	9 5	9 4	9 1				
			1 0 . 0	1 0 5	1 0 4	1 0 2	1 0 1	1 0 4	1 0 2	1 0 1	1 0 0	1 0 1	1 0 0	9 9	9 8	9 9	9 8	9 7	9 6	9 4				

