

屋内照明器具特性	
品番 (品名)	NNQ35053Z
光源	LED3000_70_3989.4 ×1 3989.4 l m
管理番号	K0169882 (0) DR 1
B Z 分類	BZ4 / 8.5 / BZ3

器具効率		1 0 0 % 上方光束 0 % 下方光束 1 0 0 %		反射率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %
					壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %
					床	1 0 %				1 0 %				1 0 %				1 0 %				0 %
				室指数		照明率 (X 0 . 0 1) Z C M																
保守率		良 中 否	0 . 6 7	0 . 6	6 0	4 9	4 1	3 6	5 9	4 8	4 1	3 6	5 7	4 7	4 1	3 6	5 5	4 6	4 0	3 6	3 4	
			0 . 6 3	0 . 8	7 0	6 0	5 2	4 7	6 9	5 9	5 2	4 7	6 6	5 8	5 1	4 7	6 4	5 6	5 1	4 7	4 5	
			1 . 0	7 7	6 7	6 0	5 5	7 5	6 6	6 0	5 5	7 3	6 5	5 9	5 4	7 0	6 3	5 8	5 4	5 2		
			0 . 5 6	1 . 2 5	8 3	7 4	6 8	6 2	8 1	7 3	6 7	6 2	7 8	7 1	6 6	6 2	7 6	7 0	6 5	6 1	5 9	
下方投影面積		c m ²	1 . 5	8 7	7 9	7 3	6 8	8 5	7 8	7 2	6 8	8 2	7 6	7 1	6 7	8 0	7 4	7 0	6 6	6 4		
			2 . 0	9 2	8 6	8 0	7 6	9 0	8 5	8 0	7 6	8 8	8 3	7 8	7 5	8 5	8 1	7 7	7 4	7 2		
等価発光面積		c m ²	2 . 5	9 5	9 0	8 5	8 1	9 4	8 9	8 5	8 1	9 1	8 7	8 3	8 0	8 8	8 5	8 2	7 9	7 7		
			3 . 0	9 7	9 3	8 9	8 5	9 6	9 2	8 8	8 5	9 3	9 0	8 6	8 4	9 1	8 8	8 5	8 2	8 0		
H m	1 . 1 8 H m	1 . 1 8 H m	4 . 0	1 0 0	9 7	9 3	9 0	9 9	9 5	9 2	9 0	9 6	9 3	9 1	8 8	9 4	9 1	8 9	8 7	8 5		
			5 . 0	1 0 2	9 9	9 6	9 4	1 0 0	9 8	9 5	9 3	9 8	9 6	9 3	9 1	9 5	9 3	9 2	9 0	8 7		
			7 . 0	1 0 4	1 0 1	9 9	9 8	1 0 2	1 0 0	9 8	9 7	1 0 0	9 8	9 7	9 5	9 7	9 6	9 5	9 3	9 1		
			1 0 . 0	1 0 5	1 0 3	1 0 2	1 0 1	1 0 4	1 0 2	1 0 1	1 0 0	1 0 1	1 0 0	9 9	9 8	9 9	9 8	9 7	9 6	9 3		

