

屋内照明器具特性	
品番 (品名)	XLF446HTN (JYOUJI)
光源	LED5000_85_3060 x1 3060.0 lm
管理番号	K0153357 (0) DR1
BZ分類	BZ9

器具効率	100 %	天井	80 %				70 %				50 %				30 %				0 %																																							
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %																																							
		床	10 %				10 %				10 %				10 %				0 %																																							
上方光束	50 %	室指数																			照明率 ( X0.01 )																			ZCM																		
下方光束	50 %																																																									
保守率	良 中 否	0.83	0.6	4.4	3.1	2.3	1.7	4.0	2.9	2.1	1.6	3.2	2.4	1.7	1.3	2.6	1.9	1.4	1.0	0.5																																						
		0.81	0.8	5.2	3.9	3.1	2.5	4.7	3.6	2.8	2.3	3.9	3.0	2.4	1.9	3.1	2.4	1.9	1.5	0.8																																						
		0.77	1.0	5.8	4.6	3.7	3.1	5.3	4.2	3.4	2.8	4.3	3.5	2.8	2.4	3.4	2.8	2.3	1.9	1.1																																						
			1.25	6.3	5.2	4.3	3.7	5.8	4.8	4.0	3.4	4.7	4.0	3.3	2.8	3.8	3.2	2.7	2.3	1.4																																						
下方投影面積		cm <sup>2</sup>																																																								
等価発光面積		cm <sup>2</sup>																																																								
取付高さ	器具間隔最大限																																																									
	横方向 (A)	縦方向 (B)																																																								
1.5m	0	2.13																																																								
2	0	2.7																																																								
2.5	0	3.3																																																								
3	0	3.91																																																								

