

屋内照明器具特性	
品番 (品名)	NSEK47732J + NEL4604HW
光源	LED4000_85_5580 ×1 5580.0 lm
管理番号	K0193800 (0) DB 1
BZ分類	BZ4

器具効率		100 %	反射率	天井	80 %				70 %				50 %				30 %				0 %			
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %			
				床	10 %				10 %				10 %				10 %				0 %			
上方光束		0 %	100 %	室指数	照明率 (X0.01)																			Z CM
下方光束																								
保守率		良 中 否	0.81	0.6	60	49	42	37	59	48	41	36	57	47	41	36	55	46	40	36	34			
			0.77	0.8	71	60	53	48	69	59	52	47	67	58	52	47	64	57	51	47	45			
			0.68	1.0	77	67	60	55	76	67	60	55	73	65	59	55	70	64	59	54	52			
				1.25	83	74	68	63	81	73	67	62	79	72	66	62	76	70	65	62	59			
下方投影面積		cm ²	1.5	87	79	73	68	85	78	72	68	82	76	71	67	80	75	70	67	64				
等価発光面積			cm ²	2.0	92	86	80	76	90	85	80	76	88	83	78	75	85	81	77	74	72			
取付 高さ	器具間隔最大限		2.5	95	90	85	81	94	89	84	81	91	87	83	80	88	85	82	79	77				
	横方向 (A)		縦方向 (B)	3.0	97	93	89	85	96	92	88	85	93	90	86	83	91	88	85	82	80			
1.5m	1.92 m	2.07 m	4.0	100	96	93	90	99	95	92	90	96	93	91	88	94	91	89	87	84				
2	2.52	2.61	5.0	102	99	96	94	100	98	95	93	98	96	93	91	95	93	92	90	87				
2.5	3.14	3.17	7.0	104	101	99	97	102	100	98	97	100	98	97	95	97	96	95	93	91				
3	3.75	3.75	10.0	105	103	102	101	104	102	101	100	101	100	99	98	99	98	97	96	93				

