

屋内照明器具特性	
品番 (品名)	NSEK47833J + NEL4600LN
光源	LED5000_85_6420 ×1 6420.0 lm
管理番号	K0193804 (0) DB 1
BZ分類	BZ4

器具効率		1 0 0 % 上方光束 0 % 下方光束 1 0 0 %	天井 壁 床 室指数	8 0 %				7 0 %				5 0 %				3 0 %				0 %
				7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %
				1 0 %				1 0 %				1 0 %				1 0 %				0 %
				照明率 (X 0 . 0 1) Z C M																
保守率		良 中 否	0 . 6	5 9	4 7	3 9	3 4	5 7	4 6	3 9	3 4	5 5	4 5	3 9	3 4	5 3	4 4	3 8	3 4	3 2
			0 . 8	6 9	5 8	5 0	4 5	6 7	5 7	5 0	4 4	6 5	5 6	4 9	4 4	6 2	5 4	4 8	4 4	4 2
			1 . 0	7 5	6 5	5 8	5 2	7 4	6 4	5 7	5 2	7 1	6 3	5 6	5 2	6 8	6 1	5 6	5 1	4 9
			0 . 6 8																	
下方投影面積 等価発光面積		c m ² c m ²	1 . 2 5	8 1	7 2	6 5	6 0	7 9	7 1	6 4	5 9	7 7	6 9	6 3	5 9	7 4	6 8	6 3	5 8	5 6
			1 . 5	8 5	7 7	7 0	6 5	8 3	7 6	7 0	6 5	8 0	7 4	6 9	6 4	7 8	7 2	6 7	6 4	6 1
			2 . 0	9 0	8 4	7 8	7 3	8 9	8 2	7 7	7 3	8 6	8 0	7 6	7 2	8 3	7 9	7 5	7 1	6 9
取付 高さ	器具間隔最大限		2 . 5	9 4	8 8	8 3	7 9	9 2	8 7	8 2	7 8	8 9	8 5	8 1	7 7	8 7	8 3	7 9	7 6	7 4
	横方向 (A) 縦方向 (B)		3 . 0	9 6	9 1	8 7	8 3	9 5	9 0	8 6	8 2	9 2	8 8	8 4	8 1	8 9	8 6	8 3	8 0	7 8
1 . 5 m	1 . 9 3 m	2 . 1 1 m	4 . 0	9 9	9 5	9 2	8 8	9 8	9 4	9 1	8 8	9 5	9 2	8 9	8 6	9 2	9 0	8 7	8 5	8 2
2	2 . 5 4	2 . 6 6	5 . 0	1 0 1	9 8	9 5	9 2	1 0 0	9 7	9 4	9 1	9 7	9 4	9 2	9 0	9 4	9 2	9 0	8 8	8 6
2 . 5	3 . 1 6	3 . 2 2	7 . 0	1 0 3	1 0 1	9 8	9 6	1 0 2	9 9	9 7	9 5	9 9	9 7	9 5	9 4	9 7	9 5	9 4	9 2	8 9
3	3 . 7 7	3 . 8	1 0 . 0	1 0 5	1 0 3	1 0 1	1 0 0	1 0 3	1 0 2	1 0 0	9 9	1 0 1	9 9	9 8	9 7	9 8	9 7	9 6	9 5	9 2

