

屋内照明器具特性

品番 (品名)	NSEK47932J + NEL4503HW																		
光源	LED4000_85_4170 ×1 4170.0 lm																		
管理番号	K0193799 (0) DB 1																		
BZ分類	BZ4 / 0.7 / BZ3																		

器具効率		1 0 0 %	反射率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %	
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %	
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %	
上方光束		0 %	室指数	照明率 (X 0 . 0 1)																		Z C M
下方光束		1 0 0 %																				
保守率		良 中 否	0 . 8 1	0 . 6	6 1	5 0	4 3	3 8	6 0	5 0	4 3	3 8	5 8	4 9	4 2	3 8	5 6	4 8	4 2	3 8	3 6	
			0 . 7 7	0 . 8	7 1	6 1	5 4	4 9	7 0	6 0	5 4	4 9	6 8	5 9	5 3	4 9	6 5	5 8	5 3	4 8	4 6	
			0 . 6 8	1 . 0	7 8	6 8	6 2	5 7	7 6	6 8	6 1	5 6	7 4	6 6	6 0	5 6	7 1	6 5	6 0	5 6	5 4	
				1 . 2 5	8 4	7 5	6 9	6 4	8 2	7 4	6 8	6 4	7 9	7 3	6 7	6 3	7 7	7 1	6 6	6 3	6 1	
下方投影面積		c m ²	1 . 5	8 7	8 0	7 4	6 9	8 6	7 9	7 3	6 9	8 3	7 7	7 2	6 8	8 0	7 5	7 1	6 8	6 5		
			等価発光面積	c m ²	2 . 0	9 2	8 6	8 1	7 7	9 1	8 5	8 0	7 6	8 8	8 3	7 9	7 6	8 6	8 1	7 8	7 5	7 2
取付高さ	器具間隔最大限		2 . 5	9 5	9 0	8 6	8 2	9 4	8 9	8 5	8 1	9 1	8 7	8 4	8 0	8 9	8 5	8 2	7 9	7 7		
	横方向 (A)		縦方向 (B)	3 . 0	9 8	9 3	8 9	8 6	9 6	9 2	8 8	8 5	9 4	9 0	8 7	8 4	9 1	8 8	8 5	8 3	8 0	
1 . 5 m	1 . 9 m	2 . 0 9 m	4 . 0	1 0 0	9 7	9 4	9 1	9 9	9 6	9 3	9 0	9 6	9 4	9 1	8 9	9 4	9 2	8 9	8 7	8 5		
2	2 . 5	2 . 6 3	5 . 0	1 0 2	9 9	9 6	9 4	1 0 1	9 8	9 5	9 3	9 8	9 6	9 4	9 2	9 6	9 4	9 2	9 0	8 8		
2 . 5	3 . 1 1	3 . 2	7 . 0	1 0 4	1 0 2	1 0 0	9 8	1 0 2	1 0 0	9 9	9 7	1 0 0	9 8	9 7	9 5	9 8	9 6	9 5	9 4	9 1		
3	3 . 7 2	3 . 7 8	1 0 . 0	1 0 5	1 0 4	1 0 2	1 0 1	1 0 4	1 0 2	1 0 1	1 0 0	1 0 1	1 0 0	9 9	9 8	9 9	9 8	9 7	9 6	9 3		

