

屋内照明器具特性	
品番 (品名)	NYM20126
光源	LED5000_85_51000 ×1 51000.0 lm
管理番号	K0165239(2)DR1
BZ分類	BZ3

器具効率	100%	天井	80%				70%				50%				30%				0%	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%	
上方光束	1%	床	10%				10%				10%				10%				0%	
下方光束	99%	室指数	照明率 (X0.01)																ZCM	
保守率	良 中 否 0.83 0.81 0.77	0.6	63	52	45	40	61	51	45	40	59	50	44	40	57	49	44	40	38	
		0.8	73	63	56	51	71	62	56	51	69	61	55	50	66	59	54	50	48	
		1.0	79	70	63	58	77	69	63	58	75	67	62	58	72	66	61	57	55	
		1.25	84	76	70	65	83	75	70	65	80	74	69	65	77	72	68	64	62	
下方投影面積	cm ²	1.5	88	81	75	70	86	80	74	70	84	78	73	69	81	76	72	69	66	
		2.0	93	87	82	78	91	86	81	77	88	84	80	76	86	82	78	75	73	
取付高さ	器具間隔最大限		2.5	96	91	86	83	94	89	85	82	91	87	84	81	89	85	82	80	77
	横方向 (A)	縦方向 (B)	3.0	98	93	89	86	96	92	89	85	93	90	87	84	91	88	85	83	80
Hm	1.19Hm	1.19Hm	4.0	100	97	94	91	99	96	93	90	96	93	91	89	93	91	89	87	84
			5.0	102	99	96	94	100	98	95	93	98	95	93	91	95	93	91	90	87
			7.0	104	101	99	98	102	100	98	97	99	98	96	95	97	95	94	93	90
			10.0	105	103	102	100	103	102	101	99	101	100	98	97	98	97	96	95	92

