

屋内照明器具特性	
品番 (品名)	NYM20144K
光源	LED5000_85_32000 ×1 32000.0 1 m
管理番号	K0165238 (1) DR 1
BZ分類	BZ2

器具効率	100 %	天井	80 %				70 %				50 %				30 %				0 %	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
上方光束	1 %	床	10 %				10 %				10 %				10 %				0 %	
下方光束	99 %	室指数	照明率 (X0.01)																ZCM	
保守率	良 中 否 0.83 0.81 0.77	0.6	71	62	56	52	70	62	56	52	68	61	56	52	66	60	55	52	50	
		0.8	79	71	65	61	78	70	65	61	76	69	64	61	74	68	64	61	59	
		1.0	84	77	72	67	83	76	71	67	81	75	70	67	79	73	69	66	65	
		1.25	89	82	77	73	87	81	77	73	85	80	76	72	83	78	75	72	70	
下方投影面積	c m ²	1.5	92	86	81	77	90	85	80	77	88	83	79	76	85	81	78	75	73	
		2.0	96	91	87	83	94	90	86	83	92	88	84	82	89	86	83	81	78	
取付高さ	器具間隔最大限		2.5	98	94	90	87	97	93	89	87	94	91	88	85	91	89	86	84	82
	横方向 (A)	縦方向 (B)	3.0	100	96	93	90	98	95	92	89	96	93	90	88	93	91	89	87	84
H m	0.92 H m	0.92 H m	4.0	102	99	96	94	100	98	95	93	98	95	93	92	95	93	92	90	87
			5.0	103	101	98	96	102	99	97	95	99	97	95	94	96	95	94	92	89
			7.0	104	103	101	99	103	101	100	98	100	99	98	97	98	97	96	95	92
			10.0	105	104	103	102	104	103	102	101	102	101	100	99	99	98	98	97	94

