

屋内照明器具特性	
品番 (品名)	NYM20144K+NYK00109
光源	LED5000_85_26400 ×1 26400.0 1m
管理番号	K0168491(0)DY1
BZ分類	BZ1/0.7/BZ2

器具効率	100%	天井	80%				70%				50%				30%				0%			
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%			
上方光束	1%	床	10%				10%				10%				10%				0%			
下方光束	99%	室指数	照明率 (X0.01) ZCM																			
保守率	良 0.77 中 0.72 否 0.68	0.6	71	62	57	53	70	62	56	53	68	61	56	52	67	60	56	52	51			
		0.8	80	72	66	62	79	71	66	62	76	70	65	62	75	69	65	62	60			
		1.0	85	78	73	69	84	77	72	69	82	76	71	68	80	75	71	68	66			
		1.25	89	83	78	75	88	82	78	74	86	81	77	74	84	80	76	73	71			
下方投影面積	c m ²	1.5	92	87	82	79	91	86	82	78	89	84	81	78	87	83	80	77	75			
		2.0	96	92	88	85	95	91	87	84	93	89	86	83	90	87	85	82	80			
取付高さ	器具間隔最大限		2.5	99	95	91	88	97	94	91	88	95	92	89	87	93	90	88	86	84		
	横方向 (A)	縦方向 (B)	3.0	100	97	94	91	99	96	93	91	96	94	92	89	94	92	90	88	86		
H m	0.93 H m	0.93 H m	4.0	102	99	97	95	101	98	96	94	98	96	95	93	96	94	93	91	89		
			5.0	103	101	99	97	102	100	98	97	100	98	96	95	97	96	95	93	91		
			7.0	105	103	102	100	103	102	101	99	101	100	99	97	99	98	97	96	93		
			10.0	106	104	103	102	104	103	102	101	102	101	100	99	100	99	98	98	95		

