

屋内照明器具特性	
品番 (品名)	NTN81020+NTN81993
光源	LED5000_70_495 ×1 495.0 lm
管理番号	K0163044 (0) DR 1
BZ分類	BZ5

器具効率		100 %	反射率	天井	80 %					70 %					50 %					30 %					0 %		
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %						
				床	10 %					10 %					10 %					10 %					0 %		
上方光束		7 %	室指数	照明率 (X0.01)																				Z	C		M
下方光束		93 %																									
保守率		良 中 否	0.69	0.6	54	42	34	29	53	41	34	28	50	40	33	28	47	38	32	27	25						
			0.67	0.8	64	52	44	38	62	51	44	38	59	49	42	37	55	47	41	37	34						
			0.63	1.0	71	60	52	46	69	58	51	45	65	56	49	44	61	54	48	43	40						
				1.25	77	67	59	53	74	65	58	52	70	62	56	51	67	60	54	50	47						
下方投影面積		cm ²	1.5	81	72	64	59	79	70	63	58	74	67	61	56	70	64	59	55	52							
等価発光面積		cm ²	2.0	86	79	72	67	84	77	71	66	80	74	69	64	76	71	66	63	59							
取付高さ	器具間隔最大限		2.5	90	83	77	73	88	81	76	72	83	78	74	70	79	75	71	68	64							
	横方向 (A)	縦方向 (B)	3.0	93	87	81	77	90	85	80	76	86	81	77	74	82	78	75	72	67							
1.5m	1.96 m	1.94 m	4.0	96	91	87	83	94	89	85	82	89	86	82	79	85	82	79	77	73							
2	2.61	2.56	5.0	98	94	90	87	96	92	88	85	91	88	85	83	87	85	82	80	76							
2.5	3.21	3.18	7.0	100	97	94	92	98	95	93	90	94	92	89	87	90	88	86	84	80							
3	3.85	3.82	10.0	102	100	98	96	100	98	96	94	96	94	92	91	92	91	89	88	83							

