

| 屋内照明器具特性 |                            |
|----------|----------------------------|
| 品番 (品名)  | NTN81021+NTN81997          |
| 光源       | LED4000_70_475 ×1 475.0 lm |
| 管理番号     | K0163044 ( 0 ) DR 1        |
| BZ分類     | BZ5                        |

| 器具効率   |         | 100 %           | 反射率  | 天井            | 80 % |    |    |     |    | 70 % |    |    |    |    | 50 % |    |    |    |    | 30 % |     |  |  |   | 0 % |  |   |
|--------|---------|-----------------|------|---------------|------|----|----|-----|----|------|----|----|----|----|------|----|----|----|----|------|-----|--|--|---|-----|--|---|
|        |         |                 |      | 壁             | 70   | 50 | 30 | 10  | 70 | 50   | 30 | 10 | 70 | 50 | 30   | 10 | 70 | 50 | 30 | 10   | 0 % |  |  |   |     |  |   |
|        |         |                 |      | 床             | 10 % |    |    |     |    | 10 % |    |    |    |    | 10 % |    |    |    |    | 10 % |     |  |  |   | 0 % |  |   |
| 上方光束   |         | 7 %             | 室指数  | 照明率 ( X0.01 ) |      |    |    |     |    |      |    |    |    |    |      |    |    |    |    |      |     |  |  | Z | C   |  | M |
| 下方光束   |         | 93 %            |      |               |      |    |    |     |    |      |    |    |    |    |      |    |    |    |    |      |     |  |  |   |     |  |   |
| 保守率    |         | 良<br>中<br>否     | 0.69 | 0.6           | 54   | 42 | 34 | 29  | 53 | 41   | 34 | 28 | 50 | 40 | 33   | 28 | 47 | 38 | 32 | 27   | 25  |  |  |   |     |  |   |
|        |         |                 | 0.67 | 0.8           | 64   | 52 | 44 | 38  | 62 | 51   | 44 | 38 | 59 | 49 | 42   | 37 | 55 | 47 | 41 | 37   | 34  |  |  |   |     |  |   |
|        |         |                 | 0.63 | 1.0           | 71   | 60 | 52 | 46  | 69 | 58   | 51 | 45 | 65 | 56 | 49   | 44 | 61 | 54 | 48 | 43   | 40  |  |  |   |     |  |   |
|        |         |                 |      | 1.25          | 77   | 67 | 59 | 53  | 74 | 65   | 58 | 52 | 70 | 62 | 56   | 51 | 67 | 60 | 54 | 50   | 47  |  |  |   |     |  |   |
| 下方投影面積 |         | cm <sup>2</sup> | 1.5  | 81            | 72   | 64 | 59 | 79  | 70 | 63   | 58 | 74 | 67 | 61 | 56   | 70 | 64 | 59 | 55 | 52   |     |  |  |   |     |  |   |
| 等価発光面積 |         | cm <sup>2</sup> | 2.0  | 86            | 79   | 72 | 67 | 84  | 77 | 71   | 66 | 80 | 74 | 69 | 64   | 76 | 71 | 66 | 63 | 59   |     |  |  |   |     |  |   |
| 取付高さ   | 器具間隔最大限 |                 | 2.5  | 90            | 83   | 77 | 73 | 88  | 81 | 76   | 72 | 83 | 78 | 74 | 70   | 79 | 75 | 71 | 68 | 64   |     |  |  |   |     |  |   |
|        | 横方向 (A) | 縦方向 (B)         | 3.0  | 93            | 87   | 81 | 77 | 90  | 85 | 80   | 76 | 86 | 81 | 77 | 74   | 82 | 78 | 75 | 72 | 67   |     |  |  |   |     |  |   |
| 1.5m   | 1.96 m  | 1.94 m          | 4.0  | 96            | 91   | 87 | 83 | 94  | 89 | 85   | 82 | 89 | 86 | 82 | 79   | 85 | 82 | 79 | 77 | 73   |     |  |  |   |     |  |   |
| 2      | 2.61    | 2.56            | 5.0  | 98            | 94   | 90 | 87 | 96  | 92 | 88   | 85 | 91 | 88 | 85 | 83   | 87 | 85 | 82 | 80 | 76   |     |  |  |   |     |  |   |
| 2.5    | 3.21    | 3.18            | 7.0  | 100           | 97   | 94 | 92 | 98  | 95 | 93   | 90 | 94 | 92 | 89 | 87   | 90 | 88 | 86 | 84 | 80   |     |  |  |   |     |  |   |
| 3      | 3.85    | 3.82            | 10.0 | 102           | 100  | 98 | 96 | 100 | 98 | 96   | 94 | 96 | 94 | 92 | 91   | 92 | 91 | 89 | 88 | 83   |     |  |  |   |     |  |   |

