

| 屋内照明器具特性 |                            |
|----------|----------------------------|
| 品番 (品名)  | NTN81031+NTN81993          |
| 光源       | LED4000_70_825 ×1 825.0 lm |
| 管理番号     | K0163044 ( 0 ) DR 1        |
| BZ分類     | BZ5                        |

| 器具効率     |           | 100 %           |           | 反射率             | 天井  | 80 %              |    |     |    | 70 % |    |    |    | 50 % |    |    |    | 30 % |    |    |    | 0 % |
|----------|-----------|-----------------|-----------|-----------------|-----|-------------------|----|-----|----|------|----|----|----|------|----|----|----|------|----|----|----|-----|
|          |           |                 |           |                 | 壁   | 70                | 50 | 30  | 10 | 70   | 50 | 30 | 10 | 70   | 50 | 30 | 10 | 70   | 50 | 30 | 10 | 0 % |
|          |           |                 |           |                 | 床   | 10 %              |    |     |    | 10 % |    |    |    | 10 % |    |    |    | 10 % |    |    |    | 0 % |
|          |           |                 |           |                 | 室指数 | 照明率 ( X0.01 ) ZCM |    |     |    |      |    |    |    |      |    |    |    |      |    |    |    |     |
| 保守率      |           | 良<br>中<br>否     | 0.69      | 0.6             | 54  | 42                | 34 | 29  | 53 | 41   | 34 | 28 | 50 | 40   | 33 | 28 | 47 | 38   | 32 | 27 | 25 |     |
|          |           |                 | 0.67      | 0.8             | 64  | 52                | 44 | 38  | 62 | 51   | 44 | 38 | 59 | 49   | 42 | 37 | 55 | 47   | 41 | 37 | 34 |     |
|          |           |                 | 1.0       | 1.0             | 71  | 60                | 52 | 46  | 69 | 58   | 51 | 45 | 65 | 56   | 49 | 44 | 61 | 54   | 48 | 43 | 40 |     |
|          |           |                 | 0.63      | 1.25            | 77  | 67                | 59 | 53  | 74 | 65   | 58 | 52 | 70 | 62   | 56 | 51 | 67 | 60   | 54 | 50 | 47 |     |
| 下方投影面積   |           | cm <sup>2</sup> | 1.5       | 81              | 72  | 64                | 59 | 79  | 70 | 63   | 58 | 74 | 67 | 61   | 56 | 70 | 64 | 59   | 55 | 52 |    |     |
|          |           |                 | 等価発光面積    | cm <sup>2</sup> | 2.0 | 86                | 79 | 72  | 67 | 84   | 77 | 71 | 66 | 80   | 74 | 69 | 64 | 76   | 71 | 66 | 63 | 59  |
| 取付<br>高さ | 器具間隔最大限   |                 |           | 2.5             | 90  | 83                | 77 | 73  | 88 | 81   | 76 | 72 | 83 | 78   | 74 | 70 | 79 | 75   | 71 | 68 | 64 |     |
|          | 横方向 ( A ) |                 | 縦方向 ( B ) | 3.0             | 93  | 87                | 81 | 77  | 90 | 85   | 80 | 76 | 86 | 81   | 77 | 74 | 82 | 78   | 75 | 72 | 67 |     |
| 1.5m     | 1.98 m    | 2.02 m          | 4.0       | 96              | 91  | 87                | 83 | 94  | 89 | 85   | 82 | 89 | 86 | 82   | 79 | 85 | 82 | 79   | 77 | 73 |    |     |
| 2        | 2.62      | 2.62            | 5.0       | 98              | 94  | 90                | 87 | 96  | 92 | 88   | 85 | 91 | 88 | 85   | 83 | 87 | 85 | 82   | 80 | 76 |    |     |
| 2.5      | 3.27      | 3.23            | 7.0       | 100             | 97  | 94                | 92 | 98  | 95 | 93   | 90 | 94 | 92 | 89   | 87 | 90 | 88 | 86   | 84 | 80 |    |     |
| 3        | 3.92      | 3.85            | 10.0      | 102             | 100 | 98                | 96 | 100 | 98 | 96   | 94 | 96 | 94 | 92   | 91 | 92 | 91 | 89   | 88 | 83 |    |     |

