

屋内照明器具特性	
品番 (品名)	NTN81300+NTN81993
光源	LED5000_70_120 ×1 120.0 l m
管理番号	K0163037 (0) DR 1
B Z 分類	BZ6 / 0.7 / BZ5 / 8.5 / BZ6

器具効率		1 0 0 %	反射率	天井	8 0 %					7 0 %					5 0 %					3 0 %					0 %
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %				
				床	1 0 %					1 0 %					1 0 %					1 0 %					0 %
上方光束		1 3 %	室指数	照明率 (X 0 . 0 1)																				Z C M	
下方光束		8 7 %																							
保守率		良 中 否	0 . 6 9	0 . 6	5 3	4 1	3 3	2 7	5 1	4 0	3 2	2 7	4 8	3 8	3 1	2 6	4 4	3 6	3 0	2 5	2 2				
			0 . 6 7	0 . 8	6 3	5 1	4 3	3 7	6 0	4 9	4 2	3 6	5 6	4 7	4 0	3 5	5 2	4 4	3 8	3 4	3 0				
			0 . 6 3	1 . 0	6 9	5 8	5 0	4 4	6 6	5 6	4 9	4 3	6 2	5 3	4 6	4 1	5 7	5 0	4 4	4 0	3 6				
				1 . 2 5	7 5	6 4	5 7	5 1	7 2	6 3	5 5	5 0	6 7	5 9	5 3	4 8	6 3	5 6	5 1	4 6	4 2				
下方投影面積		c m ²	1 . 5	7 9	6 9	6 2	5 6	7 6	6 7	6 1	5 5	7 1	6 4	5 8	5 3	6 6	6 0	5 5	5 1	4 7					
等価発光面積		c m ²	2 . 0	8 4	7 6	7 0	6 4	8 2	7 4	6 8	6 3	7 6	7 0	6 5	6 0	7 1	6 6	6 2	5 8	5 3					
取付 高さ	器具間隔最大限		2 . 5	8 8	8 1	7 5	7 0	8 5	7 9	7 3	6 8	8 0	7 4	7 0	6 6	7 5	7 0	6 6	6 3	5 8					
	横方向 (A) 縦方向 (B)		3 . 0	9 1	8 4	7 9	7 4	8 8	8 2	7 7	7 3	8 2	7 8	7 3	7 0	7 7	7 3	7 0	6 7	6 1					
H m	1 . 2 9 H m	1 . 2 4 H m	4 . 0	9 4	8 9	8 4	8 0	9 1	8 6	8 2	7 8	8 6	8 2	7 8	7 5	8 1	7 7	7 4	7 2	6 6					
			5 . 0	9 6	9 2	8 8	8 4	9 3	8 9	8 6	8 2	8 8	8 4	8 1	7 9	8 3	8 0	7 7	7 5	6 9					
			7 . 0	9 8	9 5	9 2	8 9	9 6	9 3	9 0	8 7	9 0	8 8	8 5	8 3	8 5	8 3	8 1	7 9	7 3					
			1 0 . 0	1 0 0	9 8	9 5	9 3	9 8	9 5	9 3	9 1	9 2	9 0	8 9	8 7	8 7	8 6	8 4	8 3	7 7					

