

屋内照明器具特性	
品番 (品名)	NTN81320+NTN81993
光源	LED5000_70_800 x1 800.0 lm
管理番号	K0163041 (0) DR 1
BZ分類	BZ5

器具効率		100 %	反射率	天井	80 %				70 %				50 %				30 %				0 %		
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %		
				床	10 %				10 %				10 %				10 %				0 %		
上方光束		12 %	室指数	照明率 (X0.01)																		Z	CM
下方光束		88 %																					
保守率		良 中 否	0.69	0.6	53	41	33	28	52	40	32	27	48	38	31	26	45	36	30	26	23		
			0.67	0.8	63	51	43	37	61	50	42	37	57	47	40	35	53	45	39	34	31		
			0.63	1.0	69	58	50	44	67	57	49	43	62	54	47	42	58	51	45	41	37		
				1.25	75	65	57	51	73	63	56	50	68	60	54	49	63	57	51	47	43		
下方投影面積		cm ²		1.5	79	70	62	56	77	68	61	55	72	64	58	54	67	61	56	52	47		
			等価発光面積		cm ²	2.0	85	77	70	65	82	75	69	63	77	71	66	61	72	67	63	59	54
取付 高さ	器具間隔最大限		2.5	88	81	75	70	86	79	74	69	80	75	70	66	76	71	67	64	59			
	横方向 (A) 縦方向 (B)			3.0	91	85	79	75	88	82	77	73	83	78	74	70	78	74	71	68	62		
1.5m	1.96 m	1.89 m	4.0	94	89	85	81	91	87	83	79	86	82	79	76	81	78	75	73	67			
2	2.61	2.49	5.0	96	92	88	84	94	90	86	83	88	85	82	79	83	81	78	76	70			
2.5	3.23	3.09	7.0	99	95	92	89	96	93	90	88	91	88	86	84	86	84	82	80	74			
3	3.87	3.71	10.0	101	98	96	94	98	96	94	92	93	91	89	88	88	87	85	84	78			

