

屋内照明器具特性	
品番 (品名)	NTN81334 + NTN81997K
光源	LED2700_70_1250 ×1 1250.0 lm
管理番号	K0163041 (0) DR 1
BZ分類	BZ5

器具効率		100 %	反射率	天井	80 %					70 %					50 %					30 %					0 %	
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %					
				床	10 %					10 %					10 %					10 %					0 %	
上方光束		12 %	室指数	照明率 (X0.01)																				Z	CM	
下方光束		88 %																								
保守率		良 中 否	0.69	0.6	53	41	33	28	52	40	32	27	48	38	31	26	45	36	30	26	23					
			0.67	0.8	63	51	43	37	61	50	42	37	57	47	40	35	53	45	39	34	31					
			0.63	1.0	69	58	50	44	67	57	49	43	62	54	47	42	58	51	45	41	37					
下方投影面積		cm ²	1.25	75	65	57	51	73	63	56	50	68	60	54	49	63	57	51	47	43						
			1.5	79	70	62	56	77	68	61	55	72	64	58	54	67	61	56	52	47						
等価発光面積		cm ²	2.0	85	77	70	65	82	75	69	63	77	71	66	61	72	67	63	59	54						
			2.5	88	81	75	70	86	79	74	69	80	75	70	66	76	71	67	64	59						
取付高さ	器具間隔最大限		3.0	91	85	79	75	88	82	77	73	83	78	74	70	78	74	71	68	62						
	横方向 (A)	縦方向 (B)																								
1.5m	1.98 m	1.97 m	4.0	94	89	85	81	91	87	83	79	86	82	79	76	81	78	75	73	67						
2	2.62	2.55	5.0	96	92	88	84	94	90	86	83	88	85	82	79	83	81	78	76	70						
2.5	3.27	3.15	7.0	99	95	92	89	96	93	90	88	91	88	86	84	86	84	82	80	74						
3	3.92	3.75	10.0	101	98	96	94	98	96	94	92	93	91	89	88	88	87	85	84	78						

