

屋内照明器具特性	
品番 (品名)	NTN81340 + NTN81993
光源	LED5000_70_1845 ×1 1845.0 lm
管理番号	K0163042 (0) DR 1
BZ分類	BZ5

器具効率		1 0 0 %	反射率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %
上方光束 下方光束		1 2 % 8 8 %	室指数	照明率 (X 0 . 0 1) Z C M																	
保守率		良 中 否	0 . 6 9	0 . 6	5 3	4 1	3 3	2 8	5 1	4 0	3 2	2 7	4 8	3 8	3 1	2 6	4 5	3 6	3 0	2 6	2 3
			0 . 6 7	0 . 8	6 3	5 1	4 3	3 7	6 1	5 0	4 2	3 6	5 6	4 7	4 0	3 5	5 3	4 5	3 9	3 4	3 1
			0 . 6 3	1 . 0	6 9	5 8	5 0	4 4	6 7	5 6	4 9	4 3	6 2	5 3	4 7	4 2	5 8	5 1	4 5	4 0	3 7
			0 . 6 3	1 . 2 5	7 5	6 5	5 7	5 1	7 2	6 3	5 6	5 0	6 8	6 0	5 3	4 8	6 3	5 6	5 1	4 7	4 3
下方投影面積		cm ²	1 . 5	7 9	7 0	6 2	5 6	7 6	6 8	6 1	5 5	7 1	6 4	5 8	5 3	6 7	6 1	5 6	5 1	4 7	
等価発光面積		cm ²	2 . 0	8 5	7 7	7 0	6 4	8 2	7 5	6 8	6 3	7 7	7 1	6 5	6 1	7 2	6 7	6 2	5 9	5 4	
取付 高さ	器具間隔最大限		2 . 5	8 8	8 1	7 5	7 0	8 6	7 9	7 4	6 9	8 0	7 5	7 0	6 6	7 5	7 1	6 7	6 4	5 9	
	横方向 (A)	縦方向 (B)	3 . 0	9 1	8 5	7 9	7 4	8 8	8 2	7 7	7 3	8 3	7 8	7 4	7 0	7 8	7 4	7 0	6 7	6 2	
1 . 5m	2 m	2 . 0 8 m	4 . 0	9 4	8 9	8 4	8 0	9 1	8 7	8 3	7 9	8 6	8 2	7 9	7 6	8 1	7 8	7 5	7 2	6 7	
2	2 . 6 4	2 . 6 4	5 . 0	9 6	9 2	8 8	8 4	9 3	8 9	8 6	8 3	8 8	8 5	8 2	7 9	8 3	8 1	7 8	7 6	7 0	
2 . 5	3 . 2 8	3 . 2 1	7 . 0	9 9	9 5	9 2	8 9	9 6	9 3	9 0	8 7	9 1	8 8	8 6	8 4	8 6	8 4	8 2	8 0	7 4	
3	3 . 9 2	3 . 8 1	1 0 . 0	1 0 0	9 8	9 6	9 3	9 8	9 6	9 3	9 1	9 3	9 1	8 9	8 7	8 8	8 6	8 5	8 4	7 8	

