

屋内照明器具特性	
品番 (品名)	NTN81343 + NTN81993
光源	LED3000_70_1760 ×1 1760.0 lm
管理番号	K0163042 (0) DR 1
BZ分類	BZ5

器具効率		100 %	反射率	天井	80 %				70 %				50 %				30 %				0 %			
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %			
				床	10 %				10 %				10 %				10 %				0 %			
上方光束		12 %	室指数	照明率 (X0.01)																			Z	CM
下方光束		88 %																						
保守率		良 中 否	0.69	0.6	53	41	33	28	51	40	32	27	48	38	31	26	45	36	30	26	23			
			0.67	0.8	63	51	43	37	61	50	42	36	56	47	40	35	53	45	39	34	31			
			1.0	69	58	50	44	67	56	49	43	62	53	47	42	58	51	45	40	37				
			0.63	1.25	75	65	57	51	72	63	56	50	68	60	53	48	63	56	51	47	43			
下方投影面積		cm ²	1.5	79	70	62	56	76	68	61	55	71	64	58	53	67	61	56	51	47				
			2.0	85	77	70	64	82	75	68	63	77	71	65	61	72	67	62	59	54				
等価発光面積		cm ²	2.5	88	81	75	70	86	79	74	69	80	75	70	66	75	71	67	64	59				
			3.0	91	85	79	74	88	82	77	73	83	78	74	70	78	74	70	67	62				
1.5m	2m	2.08m	4.0	94	89	84	80	91	87	83	79	86	82	79	76	81	78	75	72	67				
2	2.64	2.64	5.0	96	92	88	84	93	89	86	83	88	85	82	79	83	81	78	76	70				
2.5	3.28	3.21	7.0	99	95	92	89	96	93	90	87	91	88	86	84	86	84	82	80	74				
3	3.92	3.81	10.0	100	98	96	93	98	96	93	91	93	91	89	87	88	86	85	84	78				

