

| 屋内照明器具特性 |                              |
|----------|------------------------------|
| 品番 (品名)  | NTN81383+NTN81997K           |
| 光源       | LED3000_70_1935 ×1 1935.0 lm |
| 管理番号     | K0163042 ( 0 ) DR 1          |
| BZ分類     | BZ5                          |

| 器具効率   |         | 100 %           | 反射率     | 天井            | 80 % |    |    |    | 70 % |    |    |    | 50 % |    |    |    | 30 % |    |    |    | 0 % |  |   |   |   |
|--------|---------|-----------------|---------|---------------|------|----|----|----|------|----|----|----|------|----|----|----|------|----|----|----|-----|--|---|---|---|
|        |         |                 |         | 壁             | 70   | 50 | 30 | 10 | 70   | 50 | 30 | 10 | 70   | 50 | 30 | 10 | 70   | 50 | 30 | 10 | 0 % |  |   |   |   |
|        |         |                 |         | 床             | 10 % |    |    |    | 10 % |    |    |    | 10 % |    |    |    | 10 % |    |    |    | 0 % |  |   |   |   |
| 上方光束   |         | 12 %            | 室指数     | 照明率 ( X0.01 ) |      |    |    |    |      |    |    |    |      |    |    |    |      |    |    |    |     |  | Z | C | M |
| 下方光束   |         | 88 %            |         |               |      |    |    |    |      |    |    |    |      |    |    |    |      |    |    |    |     |  |   |   |   |
| 保守率    |         | 良<br>中<br>否     | 0.69    | 0.6           | 53   | 41 | 33 | 28 | 51   | 40 | 32 | 27 | 48   | 38 | 31 | 26 | 45   | 36 | 30 | 26 | 23  |  |   |   |   |
|        |         |                 | 0.67    | 0.8           | 63   | 51 | 43 | 37 | 61   | 50 | 42 | 36 | 56   | 47 | 40 | 35 | 53   | 45 | 39 | 34 | 31  |  |   |   |   |
|        |         |                 | 1.0     | 69            | 58   | 50 | 44 | 67 | 56   | 49 | 43 | 62 | 53   | 47 | 42 | 58 | 51   | 45 | 40 | 37 |     |  |   |   |   |
|        |         |                 | 0.63    | 1.25          | 75   | 65 | 57 | 51 | 72   | 63 | 56 | 50 | 68   | 60 | 53 | 48 | 63   | 56 | 51 | 47 | 43  |  |   |   |   |
| 下方投影面積 |         | cm <sup>2</sup> | 1.5     | 79            | 70   | 62 | 56 | 76 | 68   | 61 | 55 | 71 | 64   | 58 | 53 | 67 | 61   | 56 | 51 | 47 |     |  |   |   |   |
| 等価発光面積 |         | cm <sup>2</sup> | 2.0     | 85            | 77   | 70 | 64 | 82 | 75   | 68 | 63 | 77 | 71   | 65 | 61 | 72 | 67   | 62 | 59 | 54 |     |  |   |   |   |
| 取付高さ   | 器具間隔最大限 |                 | 2.5     | 88            | 81   | 75 | 70 | 86 | 79   | 74 | 69 | 80 | 75   | 70 | 66 | 75 | 71   | 67 | 64 | 59 |     |  |   |   |   |
|        | 横方向 (A) |                 | 縦方向 (B) | 3.0           | 91   | 85 | 79 | 74 | 88   | 82 | 77 | 73 | 83   | 78 | 74 | 70 | 78   | 74 | 70 | 67 | 62  |  |   |   |   |
| 1.5m   | 2.01 m  | 2.13 m          | 4.0     | 94            | 89   | 84 | 80 | 91 | 87   | 83 | 79 | 86 | 82   | 79 | 76 | 81 | 78   | 75 | 72 | 67 |     |  |   |   |   |
| 2      | 2.64    | 2.68            | 5.0     | 96            | 92   | 88 | 84 | 93 | 89   | 86 | 83 | 88 | 85   | 82 | 79 | 83 | 81   | 78 | 76 | 70 |     |  |   |   |   |
| 2.5    | 3.29    | 3.25            | 7.0     | 99            | 95   | 92 | 89 | 96 | 93   | 90 | 87 | 91 | 88   | 86 | 84 | 86 | 84   | 82 | 80 | 74 |     |  |   |   |   |
| 3      | 3.92    | 3.83            | 10.0    | 100           | 98   | 96 | 93 | 98 | 96   | 93 | 91 | 93 | 91   | 89 | 87 | 88 | 86   | 85 | 84 | 78 |     |  |   |   |   |

