

屋内照明器具特性	
品番 (品名)	NTN82083K+NTS90351
光源	LED3000_70_1155 x1 1155.0 lm
管理番号	K0179727 (0) DR 1
BZ分類	BZ1

器具効率	1 0 0 %	反 射 率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %	
			壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %	
			床	1 0 %				1 0 %				1 0 %				1 0 %				0 %	
上方光束	0 %	室指数	照明率 (X 0 . 0 1)																		Z C M
下方光束	1 0 0 %																				
保守率	良	0 . 6 3	0 . 6	8 2	7 6	7 2	6 9	8 2	7 6	7 2	6 9	8 0	7 5	7 1	6 9	7 9	7 4	7 1	6 9	6 8	
	中	0 . 6	0 . 8	8 9	8 3	7 9	7 6	8 8	8 3	7 9	7 6	8 6	8 2	7 8	7 6	8 5	8 1	7 8	7 6	7 5	
	否	0 . 5 6	1 . 0	9 3	8 8	8 4	8 1	9 2	8 7	8 4	8 1	9 0	8 6	8 3	8 1	8 8	8 5	8 2	8 0	7 9	
			1 . 2 5	9 6	9 1	8 8	8 6	9 5	9 1	8 8	8 5	9 3	9 0	8 7	8 5	9 1	8 8	8 6	8 4	8 3	
下方投影面積	c m ²		1 . 5	9 8	9 4	9 1	8 9	9 7	9 3	9 1	8 8	9 5	9 2	9 0	8 8	9 3	9 1	8 9	8 7	8 5	
等価発光面積	c m ²		2 . 0	1 0 1	9 7	9 5	9 3	1 0 0	9 7	9 4	9 2	9 8	9 5	9 3	9 1	9 6	9 4	9 2	9 1	8 9	
取付 高さ	器具間隔最大限		2 . 5	1 0 2	1 0 0	9 7	9 5	1 0 1	9 9	9 7	9 5	9 9	9 7	9 5	9 4	9 7	9 6	9 4	9 3	9 1	
	横方向 (A)	縦方向 (B)	3 . 0	1 0 3	1 0 1	9 9	9 7	1 0 2	1 0 0	9 8	9 7	1 0 0	9 8	9 7	9 6	9 8	9 7	9 6	9 4	9 2	
H m	0 . 3 5 H m	0 . 7 9 H m	4 . 0	1 0 5	1 0 3	1 0 1	1 0 0	1 0 4	1 0 2	1 0 0	9 9	1 0 1	1 0 0	9 9	9 8	9 9	9 8	9 7	9 6	9 4	
			5 . 0	1 0 5	1 0 4	1 0 3	1 0 1	1 0 4	1 0 3	1 0 2	1 0 1	1 0 2	1 0 1	1 0 0	9 9	1 0 0	9 9	9 8	9 8	9 5	
			7 . 0	1 0 6	1 0 5	1 0 4	1 0 3	1 0 5	1 0 4	1 0 3	1 0 3	1 0 3	1 0 2	1 0 2	1 0 1	1 0 1	1 0 0	1 0 0	9 9	9 7	
			1 0 . 0	1 0 7	1 0 6	1 0 6	1 0 5	1 0 6	1 0 5	1 0 5	1 0 4	1 0 4	1 0 3	1 0 3	1 0 2	1 0 2	1 0 1	1 0 1	1 0 0	9 8	

