

屋内照明器具特性	
品番 (品名)	NTN82104Z+NTS90201
光源	LED2700_70_400 ×1 400.0 l m
管理番号	K0197379 (0) DR 1
B Z 分類	BZ1

器具効率		100 %	反 射 率	天井	80 %				70 %				50 %				30 %				0 %	
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
				床	10 %				10 %				10 %				10 %				0 %	
上方光束		0 %	室指数	照明率 (X0.01)																		Z C M
下方光束		100 %																				
保守率		良	0.63	0.6	73	64	59	55	72	64	59	55	70	63	58	55	69	62	58	55	53	
		中	0.6	0.8	81	74	68	65	80	73	68	65	78	72	68	64	77	71	67	64	63	
		否	1.0	87	80	75	71	85	79	74	71	83	78	74	70	81	77	73	70	69		
		0.56	1.25	91	85	80	77	90	84	80	77	88	83	79	76	86	81	78	76	74		
下方投影面積		c m ²		1.5	94	89	84	81	93	88	84	81	90	86	83	80	88	85	82	80	78	
等価発光面積		c m ²		2.0	98	93	90	87	96	92	89	86	94	91	88	86	92	89	87	85	83	
取付 高さ	器具間隔最大限			2.5	100	96	93	91	99	95	93	90	96	94	91	89	94	92	90	88	86	
	横方向 (A)		縦方向 (B)	3.0	101	98	96	93	100	97	95	93	98	95	93	91	96	94	92	90	88	
H m	0.43 H m		1.02 H m	4.0	103	101	99	97	102	100	98	96	100	98	96	95	97	96	95	93	91	
				5.0	104	102	100	99	103	101	100	98	101	99	98	97	99	97	96	95	93	
				7.0	105	104	103	101	104	103	102	101	102	101	100	99	100	99	98	97	95	
				10.0	106	105	104	103	105	104	103	102	103	102	101	101	100	99	99	96		

