

屋内照明器具特性	
品番 (品名)	NTN83054
光源	LED2700_70_860 ×1 860.0 lm
管理番号	K0169805 (0) DY 1
BZ分類	BZ6

器具効率		100 %	反射率	天井	80 %					70 %					50 %					30 %					0 %					
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %									
				床	10 %					10 %					10 %					10 %					0 %					
上方光束		16 %	室指数	照明率 (X0.01)																				Z	C					M
下方光束		84 %																												
保守率		良 中 否	0.69	0.6	52	39	31	25	49	38	30	25	45	35	29	24	42	33	27	23	20									
			0.67	0.8	61	49	40	34	58	47	39	34	54	44	37	32	49	41	35	31	27									
			0.63	1.0	67	56	47	41	64	54	46	40	59	50	44	38	55	47	41	37	33									
				1.25	73	62	54	48	70	60	53	47	65	56	50	45	60	53	47	43	38									
下方投影面積		cm ²	1.5	77	67	59	53	74	65	58	52	68	61	55	50	63	57	52	47	42										
等価発光面積		cm ²	2.0	83	74	67	61	80	72	65	60	74	67	62	57	68	63	58	54	49										
取付 高さ	器具間隔最大限		2.5	86	79	73	67	83	76	71	65	77	72	67	62	72	67	63	59	54										
	横方向 (A)		縦方向 (B)	3.0	89	82	77	72	86	80	74	70	80	75	70	66	74	70	66	63	57									
1.5m	2.03 m	1.96 m	4.0	92	87	82	78	89	84	80	76	83	79	75	72	78	74	71	68	62										
2	2.7	2.59	5.0	95	90	86	82	91	87	83	80	85	82	79	76	80	77	74	72	65										
2.5	3.4	3.22	7.0	97	94	90	87	94	91	88	85	88	85	83	80	83	80	78	76	69										
3	4.05	3.84	10.0	99	96	94	91	96	94	91	89	90	88	86	84	85	83	81	80	73										

