

屋内照明器具特性	
品番 (品名)	NTN83180
光源	LED5000_70_370 x1 370.0 lm
管理番号	K0167957 (0) DY1
BZ分類	BZ6

器具効率		100 %	反射率	天井	80 %					70 %					50 %					30 %					0 %	
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %					
				床	10 %					10 %					10 %					10 %					0 %	
上方光束		22 %	室指数	照明率 (X0.01)																				Z	C	M
下方光束		78 %																								
保守率		良 中 否	0.69	0.6	49	37	29	23	47	35	28	22	42	32	26	21	38	30	24	20	16					
			0.67	0.8	58	46	38	31	56	44	36	31	50	41	34	29	45	37	31	27	23					
			1.0	65	53	44	38	61	51	43	37	55	46	40	35	50	43	37	32	27						
			0.63	1.25	70	59	51	45	67	57	49	43	60	52	46	41	55	48	42	38	33					
下方投影面積		cm ²	1.5	74	64	56	50	71	62	54	48	64	57	50	45	58	52	47	42	36						
			2.0	80	71	64	58	76	68	62	56	69	63	57	53	63	58	53	49	42						
等価発光面積	cm ²	2.5	84	76	69	64	80	73	67	62	73	67	62	58	66	62	57	54	47							
		3.0	87	80	73	68	83	76	71	66	76	70	66	62	69	65	61	57	50							
1.5m	2.2 m	1.96 m	4.0	90	84	79	75	86	81	76	72	79	75	71	67	72	69	66	63	55						
2	2.93	2.57	5.0	92	87	83	79	88	84	80	76	81	78	74	71	74	71	69	66	58						
2.5	3.67	3.2	7.0	95	91	87	84	91	88	84	81	84	81	78	76	77	75	73	71	62						
3	4.45	3.83	10.0	97	94	91	89	93	91	88	86	86	84	82	80	79	78	76	74	66						

