

# 屋内照明器具特性

品番 (品名)	XFL312DT										
光源	LDL40S.N/14/26(2600A) ×1 2600.0 1m										
管理番号	K0126619(7)DB1										
BZ分類	BZ5/0.7/BZ4										

器具効率	91%	天井	80%				70%				50%				30%				0%																																	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%																																	
		床	10%				10%				10%				10%				0%																																	
上方光束	0%	室指数																	照明率 (X0.01)																	ZCM																
下方光束	91%																																																			
保守率	良 中 否	0.81	0.6	53	42	35	30	52	41	35	30	50	41	34	30	48	40	34	30	28																																
		0.77	0.8	62	53	46	41	61	52	45	41	59	51	45	40	57	50	44	40	38																																
			1.0	69	60	53	48	67	59	53	48	65	57	52	48	63	56	51	47	45																																
		0.68	1.25	74	66	60	55	73	65	60	55	70	64	59	55	68	62	58	54	52																																
下方投影面積	c m <sup>2</sup>	1.5	78	71	65	60	76	70	64	60	74	68	63	59	71	66	62	59	57																																	
		2.0	83	77	72	68	81	76	71	67	79	74	70	67	76	72	69	66	64																																	
等価発光面積	c m <sup>2</sup>	2.5	86	81	76	73	84	80	76	72	82	78	74	71	79	76	73	70	68																																	
		3.0	88	83	80	76	86	82	79	76	84	80	77	75	82	79	76	74	71																																	
取付高さ	器具間隔最大限		4.0	90	87	84	81	89	86	83	80	87	84	81	79	84	82	80	78	76																																
	横方向 (A)	縦方向 (B)	5.0	92	89	86	84	91	88	86	83	88	86	84	82	86	84	82	81	78																																
1.5m	2.07m	2.19m	7.0	94	92	90	88	92	91	89	87	90	89	87	86	88	87	85	84	82																																
2	2.74	2.77	10.0	95	94	92	91	94	92	91	90	92	90	89	88	89	88	88	87	84																																
2.5	3.41	3.36																																																		
3	4.07	3.97																																																		

