

| | |
|----------|-----------------------------------|
| 屋内照明器具特性 | |
| 品番 (品名) | XFL312TCB |
| 光源 | LDL40S.N/14/26(2600A) ×1 2600.0lm |
| 管理番号 | K0126758(1)DR1 |
| BZ分類 | BZ4/0.7/BZ3/1.8/BZ4 |

| | | | | | | | | | | | | | | | | | | | | |
|--------|----------------------------|---------|-------------|----|----|----|-----|----|----|----|-----|----|----|----|-----|----|----|----|-----|----|
| 器具効率 | 83% | 天井 | 80% | | | | 70% | | | | 50% | | | | 30% | | | | 0% | |
| | | 壁 | 70 | 50 | 30 | 10 | 70 | 50 | 30 | 10 | 70 | 50 | 30 | 10 | 70 | 50 | 30 | 10 | 0% | |
| 上方光束 | 0% | 床 | 10% | | | | 10% | | | | 10% | | | | 10% | | | | 0% | |
| 下方光束 | 83% | 室指数 | 照明率 (X0.01) | | | | | | | | | | | | | | | | ZCM | |
| 保守率 | 良 0.81 中 0.77 否 0.68 | 0.6 | 51 | 41 | 35 | 31 | 50 | 41 | 35 | 31 | 48 | 40 | 35 | 31 | 46 | 39 | 34 | 31 | 29 | |
| | | 0.8 | 59 | 50 | 45 | 40 | 58 | 50 | 44 | 40 | 56 | 49 | 44 | 40 | 54 | 48 | 43 | 40 | 38 | |
| | | 1.0 | 64 | 57 | 51 | 47 | 63 | 56 | 51 | 47 | 61 | 55 | 50 | 46 | 59 | 54 | 49 | 46 | 44 | |
| | | 1.25 | 69 | 62 | 57 | 53 | 68 | 61 | 57 | 53 | 66 | 60 | 56 | 52 | 64 | 59 | 55 | 52 | 50 | |
| 下方投影面積 | c m ² | 1.5 | 72 | 66 | 61 | 57 | 71 | 65 | 61 | 57 | 69 | 64 | 60 | 56 | 67 | 62 | 59 | 56 | 54 | |
| | | 2.0 | 76 | 71 | 67 | 63 | 75 | 70 | 66 | 63 | 73 | 69 | 65 | 62 | 71 | 67 | 64 | 62 | 60 | |
| 取付高さ | 器具間隔最大限 | | 2.5 | 79 | 75 | 71 | 68 | 78 | 74 | 70 | 67 | 76 | 72 | 69 | 66 | 73 | 70 | 68 | 66 | 64 |
| | 横方向 (A) | 縦方向 (B) | 3.0 | 81 | 77 | 74 | 71 | 80 | 76 | 73 | 70 | 77 | 74 | 72 | 69 | 75 | 73 | 70 | 68 | 66 |
| 1.5m | 2.03m | 2.05m | 4.0 | 83 | 80 | 77 | 75 | 82 | 79 | 77 | 74 | 80 | 77 | 75 | 73 | 78 | 76 | 74 | 72 | 70 |
| 2 | 2.69 | 2.56 | 5.0 | 84 | 82 | 80 | 77 | 83 | 81 | 79 | 77 | 81 | 79 | 77 | 76 | 79 | 77 | 76 | 74 | 72 |
| 2.5 | 3.34 | 3.1 | 7.0 | 86 | 84 | 82 | 81 | 85 | 83 | 81 | 80 | 83 | 81 | 80 | 79 | 81 | 79 | 78 | 77 | 75 |
| 3 | 3.99 | 3.65 | 10.0 | 87 | 86 | 84 | 83 | 86 | 85 | 84 | 82 | 84 | 83 | 82 | 81 | 82 | 81 | 80 | 79 | 77 |

