

屋内照明器具特性	
品番 (品名)	XFL323ZP
光源	LDL40S.N/29/31-9(3150A) ×2 3150.0 1m
管理番号	K0126763(1)DR1
BZ分類	BZ3/4.5/BZ4

器具効率	73%	天井	80%				70%				50%				30%				0%	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%	
上方光束	0%	床	10%				10%				10%				10%				0%	
下方光束	73%	室指数	照明率 (X0.01)																ZCM	
保守率	良	0.86	0.6	4.6	3.8	3.3	2.9	4.5	3.8	3.3	2.9	4.3	3.7	3.2	2.9	4.2	3.6	3.2	2.9	2.8
	中	0.81	0.8	5.3	4.6	4.1	3.7	5.2	4.5	4.1	3.7	5.0	4.4	4.0	3.7	4.9	4.3	4.0	3.7	3.5
	否	0.76	1.0	5.8	5.1	4.6	4.3	5.7	5.0	4.6	4.2	5.5	4.9	4.5	4.2	5.3	4.8	4.5	4.2	4.1
			1.25	6.2	5.6	5.1	4.8	6.1	5.5	5.1	4.8	5.9	5.4	5.0	4.7	5.7	5.3	4.9	4.7	4.5
下方投影面積		cm <sup>2</sup>	1.5	6.4	5.9	5.5	5.1	6.3	5.8	5.4	5.1	6.1	5.7	5.3	5.1	5.9	5.6	5.3	5.0	4.9
等価発光面積		cm <sup>2</sup>	2.0	6.8	6.3	6.0	5.7	6.7	6.3	5.9	5.6	6.5	6.1	5.8	5.6	6.3	6.0	5.7	5.5	5.3
取付高さ	器具間隔最大限		2.5	7.0	6.6	6.3	6.0	6.9	6.5	6.2	6.0	6.7	6.4	6.1	5.9	6.5	6.2	6.0	5.8	5.7
	横方向 (A)	縦方向 (B)	3.0	7.1	6.8	6.5	6.3	7.0	6.7	6.5	6.2	6.8	6.6	6.3	6.1	6.6	6.4	6.2	6.1	5.9
1.5m	1.78m	2.03m	4.0	7.3	7.1	6.8	6.6	7.2	7.0	6.8	6.6	7.0	6.8	6.6	6.5	6.8	6.7	6.5	6.4	6.2
2	2.36	2.57	5.0	7.4	7.2	7.0	6.8	7.3	7.1	6.9	6.8	7.1	7.0	6.8	6.7	7.0	6.8	6.7	6.6	6.4
2.5	2.94	3.12	7.0	7.6	7.4	7.2	7.1	7.5	7.3	7.2	7.0	7.3	7.1	7.0	6.9	7.1	7.0	6.9	6.8	6.6
3	3.51	3.69	10.0	7.7	7.5	7.4	7.3	7.6	7.5	7.4	7.3	7.4	7.3	7.2	7.1	7.2	7.1	7.1	7.0	6.8

