

屋内照明器具特性

品番 (品名)	XLX400NEW										
光源	LED4000_85_9530 x1 9530.0lm										
管理番号	K0159374(0)D1										
BZ分類	BZ5										

器具効率	100%	天井	80%				70%				50%				30%				0%	
			壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
上方光束	4%	反射率	床	10%				10%				10%				10%				0%
下方光束	96%		室指数	照明率 (X0.01) ZCM																
保守率	良 中 否 0.83 0.81 0.77	0.6	5.5	4.3	3.5	2.9	5.4	4.2	3.4	2.9	5.1	4.1	3.4	2.9	4.8	3.9	3.3	2.8	2.6	
		0.8	6.5	5.3	4.5	3.9	6.3	5.2	4.5	3.9	6.0	5.0	4.4	3.8	5.7	4.9	4.3	3.8	3.5	
		1.0	7.1	6.0	5.2	4.6	7.0	5.9	5.2	4.6	6.6	5.7	5.0	4.5	6.3	5.5	4.9	4.5	4.2	
		1.25	7.7	6.7	6.0	5.4	7.5	6.6	5.9	5.3	7.2	6.4	5.7	5.2	6.8	6.1	5.6	5.1	4.8	
下方投影面積	c m ²	1.5	8.1	7.2	6.5	5.9	7.9	7.1	6.4	5.9	7.6	6.8	6.2	5.7	7.2	6.6	6.1	5.6	5.3	
		2.0	8.7	7.9	7.3	6.7	8.5	7.8	7.2	6.7	8.1	7.5	7.0	6.5	7.7	7.2	6.8	6.4	6.1	
取付高さ	器具間隔最大限		2.5	9.1	8.4	7.8	7.3	8.9	8.2	7.7	7.2	8.5	7.9	7.5	7.1	8.1	7.7	7.3	6.9	6.6
	横方向 (A)	縦方向 (B)	3.0	9.3	8.7	8.2	7.7	9.1	8.6	8.1	7.6	8.7	8.3	7.8	7.5	8.4	8.0	7.6	7.3	7.0
1.5m	1.98m	2.12m	4.0	9.6	9.1	8.7	8.3	9.4	9.0	8.6	8.2	9.1	8.7	8.3	8.0	8.7	8.4	8.1	7.8	7.5
2	2.61	2.66	5.0	9.8	9.4	9.1	8.7	9.6	9.3	8.9	8.6	9.3	9.0	8.7	8.4	8.9	8.7	8.4	8.2	7.8
2.5	3.25	3.23	7.0	10.1	9.8	9.5	9.2	9.9	9.6	9.3	9.1	9.5	9.3	9.1	8.8	9.2	9.0	8.8	8.6	8.2
3	3.88	3.81	10.0	10.3	10.0	9.8	9.6	10.1	9.9	9.7	9.5	9.7	9.5	9.4	9.2	9.4	9.2	9.1	9.0	8.6

