

屋内照明器具特性

品番 (品名)	XLF436NTN(JYOUJI_CEILING)									
光源	LED5000_85_3070 x1 3070.0 1m									
管理番号	K0153233(4)DB1									
BZ分類	BZ6/0.7/BZ5/3.5/BZ6/4.5/BZ5 /6.0/BZ6									

器具効率	100%	天井	80%				70%				50%				30%				0%		
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%		
		床	10%				10%				10%				10%				0%		
上方光束	9%																				
下方光束	91%																				
		室指数	照明率 (X0.01) ZCM																		
保守率	良 中 否	0.83	0.6	53	41	33	27	52	40	32	27	48	38	31	26	45	36	30	26	23	
		0.81	0.8	63	51	42	36	61	50	42	36	57	47	40	35	53	45	39	34	31	
			1.0	69	58	50	43	67	56	49	43	63	54	47	42	59	51	45	41	37	
		0.77	1.25	75	65	57	50	73	63	56	50	68	60	54	48	64	57	52	47	43	
下方投影面積		cm ²																			
等価発光面積		cm ²																			
取付高さ	器具間隔最大限																				
	横方向 (A)	縦方向 (B)																			
1.5m	1.97m	2.1m	4.0	94	89	84	80	92	87	83	79	87	83	80	76	83	79	76	74	69	
2	2.61	2.67	5.0	96	92	88	84	94	90	86	83	89	86	83	80	85	82	80	77	72	
2.5	3.24	3.25	7.0	99	96	92	89	97	93	91	88	92	89	87	85	88	86	84	82	76	
3	3.88	3.86	10.0	101	98	96	94	99	96	94	92	94	92	90	89	90	88	87	85	80	

