

|          |                                  |
|----------|----------------------------------|
| 屋内照明器具特性 |                                  |
| 品番(品名)   | LGB15061WZ                       |
| 光源       | LDA7L-G/Z60E/S/W/2 × 1 810.0 l m |
| 管理番号     | K0126485(0)DB1                   |
| BZ分類     | BZ8                              |

|        |         |        |               |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |
|--------|---------|--------|---------------|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|
| 器具効率   | 91%     | 天井     | 80%           |     |     |     | 70% |     |     |     | 50% |     |     |     | 30% |     |     |     | 0%  |     |
|        |         |        | 壁             | 70  | 50  | 30  | 10  | 70  | 50  | 30  | 10  | 70  | 50  | 30  | 10  | 70  | 50  | 30  | 10  | 0%  |
| 上方光束   | 38%     | 床      | 10%           |     |     |     | 10% |     |     |     | 10% |     |     |     | 10% |     |     |     | 0%  |     |
| 下方光束   | 53%     |        | 10%           |     |     |     | 10% |     |     |     | 10% |     |     |     | 10% |     |     |     | 0%  |     |
|        |         | 室指数    | 照明率 ( X0.01 ) |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     | ZCM |     |
| 保守率    | 良       | 0.63   | 0.6           | 4.2 | 3.0 | 2.3 | 1.8 | 3.8 | 2.8 | 2.2 | 1.7 | 3.3 | 2.4 | 1.9 | 1.5 | 2.7 | 2.1 | 1.6 | 1.2 | 8   |
|        | 中       | 0.6    | 0.8           | 4.9 | 3.8 | 3.0 | 2.5 | 4.6 | 3.5 | 2.8 | 2.3 | 3.9 | 3.0 | 2.5 | 2.0 | 3.2 | 2.6 | 2.1 | 1.7 | 1.2 |
|        | 否       | 0.56   | 1.0           | 5.5 | 4.4 | 3.6 | 3.0 | 5.0 | 4.1 | 3.4 | 2.8 | 4.3 | 3.5 | 2.9 | 2.5 | 3.6 | 3.0 | 2.5 | 2.1 | 1.5 |
|        |         |        | 1.25          | 6.0 | 5.0 | 4.2 | 3.6 | 5.5 | 4.6 | 3.9 | 3.4 | 4.7 | 4.0 | 3.4 | 3.0 | 3.9 | 3.4 | 2.9 | 2.5 | 1.8 |
| 下方投影面積 |         | 等価発光面積 | 1.5           | 6.3 | 5.4 | 4.6 | 4.1 | 5.9 | 5.0 | 4.4 | 3.8 | 5.0 | 4.3 | 3.8 | 3.3 | 4.2 | 3.7 | 3.2 | 2.9 | 2.1 |
|        |         |        | 2.0           | 6.8 | 6.0 | 5.3 | 4.8 | 6.3 | 5.6 | 5.0 | 4.5 | 5.4 | 4.8 | 4.3 | 3.9 | 4.6 | 4.1 | 3.7 | 3.4 | 2.5 |
| 取付高さ   | 器具間隔最大限 |        | 2.5           | 7.2 | 6.4 | 5.8 | 5.3 | 6.7 | 6.0 | 5.5 | 5.0 | 5.7 | 5.2 | 4.7 | 4.4 | 4.8 | 4.4 | 4.1 | 3.7 | 2.8 |
|        | 横方向(A)  | 縦方向(B) | 3.0           | 7.4 | 6.8 | 6.2 | 5.7 | 6.9 | 6.3 | 5.8 | 5.4 | 5.9 | 5.5 | 5.1 | 4.7 | 5.0 | 4.7 | 4.3 | 4.0 | 3.0 |
| Hm     | 1.50Hm  | 1.50Hm | 4.0           | 7.7 | 7.2 | 6.7 | 6.3 | 7.2 | 6.7 | 6.3 | 5.9 | 6.2 | 5.8 | 5.5 | 5.2 | 5.3 | 5.0 | 4.7 | 4.5 | 3.4 |
|        |         |        | 5.0           | 7.9 | 7.5 | 7.0 | 6.6 | 7.4 | 7.0 | 6.6 | 6.3 | 6.4 | 6.1 | 5.8 | 5.5 | 5.5 | 5.2 | 5.0 | 4.8 | 3.6 |
|        |         |        | 7.0           | 8.2 | 7.8 | 7.5 | 7.1 | 7.7 | 7.3 | 7.0 | 6.7 | 6.7 | 6.4 | 6.1 | 5.9 | 5.7 | 5.5 | 5.3 | 5.1 | 3.9 |
|        |         |        | 10.0          | 8.4 | 8.1 | 7.8 | 7.6 | 7.9 | 7.6 | 7.4 | 7.1 | 6.9 | 6.7 | 6.5 | 6.3 | 5.9 | 5.8 | 5.6 | 5.5 | 4.2 |

