

屋内照明器具特性

品番 (品名)	XNG1561WV(J O U J I)				
光源	LED3500_85_1510 x1 1510.0 lm				
管理番号	K0160264(0)DB1				
BZ分類	BZ2/0.7/BZ1/4.5/BZ2/6.0/BZ1				

器具効率	100%	天井	80%				70%				50%				30%				0%	
	上方光束 0%		反射率	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
下方光束	100%	床		10%				10%				10%				10%				0%
室指数	照明率 (X0.01)																			ZCM
保守率	良	0.81	0.6	71	61	56	52	70	61	55	52	68	60	55	51	66	59	55	51	50
	中	0.77	0.8	80	72	67	63	79	72	67	63	77	71	66	63	75	70	65	62	61
	否	0.68	1.0	86	79	74	70	85	78	74	70	83	77	73	70	81	76	72	69	68
			1.25	91	85	80	77	90	84	80	76	87	83	79	76	85	81	78	75	74
下方投影面積			1.5	94	88	84	81	93	88	84	80	90	86	83	80	88	85	82	79	77
			2.0	97	93	90	87	96	92	89	86	94	91	88	85	92	89	87	85	83
取付高さ	器具間隔最大限		2.5	100	96	93	90	99	95	92	90	96	93	91	89	94	92	90	88	86
	横方向 (A)	縦方向 (B)	3.0	101	98	95	93	100	97	95	92	98	95	93	91	96	94	92	90	88
Hm	1.27Hm	1.28Hm	4.0	103	101	98	97	102	100	98	96	100	98	96	95	97	96	94	93	91
			5.0	104	102	100	99	103	101	99	98	101	99	98	96	98	97	96	95	93
			7.0	105	104	103	101	104	103	102	100	102	101	100	99	100	99	98	97	95
			10.0	106	105	104	103	105	104	103	102	103	102	101	101	100	99	99	99	96

