

# 屋内照明器具特性

品番 (品名)	XLGB1221		
光源	LLD20001CQ1 ×1	531.0 lm	
管理番号	K0176322(0)DR1		
BZ分類	BZ3		

器具効率	75%	天井	80%				70%				50%				30%				0%	
	上方光束 0%		反射率	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
				下方光束 75%	10%				10%				10%				10%			
室指数	照明率 (X0.01)																			ZCM
保守率	良 0.67	0.6	49	42	37	34	49	41	37	33	47	41	36	33	46	40	36	33	32	
	中 0.63	0.8	56	49	44	40	55	48	44	40	53	48	43	40	52	47	43	40	39	
	否 0.56	1.0	60	54	49	45	59	53	49	45	57	52	48	45	56	51	47	45	43	
	下方投影面積 等価発光面積	c m <sup>2</sup>	1.25	64	58	54	50	63	57	53	50	61	56	53	50	59	55	52	49	48
取付 高さ H m	器具間隔最大限		2.5	72	68	65	62	71	68	65	62	69	66	64	61	67	65	62	61	59
	横方向 (A)	縦方向 (B)	3.0	74	70	67	65	73	70	67	65	71	68	66	64	69	67	65	63	61
	1.32 H m	1.32 H m	4.0	76	73	71	69	75	72	70	68	73	71	69	67	71	69	67	66	64
			5.0	77	75	73	71	76	74	72	70	74	72	71	69	72	71	69	68	66
			7.0	78	76	75	74	77	76	74	73	75	74	73	72	73	72	71	70	68
			10.0	79	78	77	76	78	77	76	75	76	75	74	74	74	74	73	72	70

