

# 屋内照明器具特性

|         |                               |  |  |  |  |  |  |  |  |  |
|---------|-------------------------------|--|--|--|--|--|--|--|--|--|
| 品番 (品名) | P M L E L 1 2 0 5 0 F S       |  |  |  |  |  |  |  |  |  |
| 光源      | LED5000_70_3260 x1 3260.0 1 m |  |  |  |  |  |  |  |  |  |
| 管理番号    | K0176993 ( 0 ) DY 1           |  |  |  |  |  |  |  |  |  |
| B Z 分類  | BZ5 / 0.7 / BZ4               |  |  |  |  |  |  |  |  |  |

|        |         |         |               |     |     |     |      |     |     |    |      |     |    |    |      |    |    |    |     |    |
|--------|---------|---------|---------------|-----|-----|-----|------|-----|-----|----|------|-----|----|----|------|----|----|----|-----|----|
| 器具効率   | 100 %   | 天井      | 80 %          |     |     |     | 70 % |     |     |    | 50 % |     |    |    | 30 % |    |    |    | 0 % |    |
|        |         | 壁       | 70            | 50  | 30  | 10  | 70   | 50  | 30  | 10 | 70   | 50  | 30 | 10 | 70   | 50 | 30 | 10 | 0 % |    |
| 上方光束   | 2 %     | 床       | 10 %          |     |     |     | 10 % |     |     |    | 10 % |     |    |    | 10 % |    |    |    | 0 % |    |
| 下方光束   | 98 %    | 室指数     | 照明率 ( X0.01 ) |     |     |     |      |     |     |    |      |     |    |    |      |    |    |    | ZCM |    |
| 保守率    | 良       | 0.69    | 0.6           | 58  | 46  | 39  | 33   | 57  | 46  | 38 | 33   | 54  | 44 | 38 | 33   | 52 | 43 | 37 | 33  | 31 |
|        | 中       | 0.67    | 0.8           | 68  | 57  | 50  | 44   | 67  | 56  | 49 | 44   | 64  | 55 | 48 | 43   | 61 | 53 | 47 | 43  | 41 |
|        | 否       | 0.63    | 1.0           | 75  | 65  | 57  | 52   | 73  | 64  | 57 | 51   | 70  | 62 | 56 | 51   | 67 | 60 | 55 | 50  | 48 |
|        |         |         | 1.25          | 81  | 72  | 65  | 59   | 79  | 70  | 64 | 59   | 76  | 68 | 63 | 58   | 73 | 67 | 62 | 58  | 55 |
| 下方投影面積 |         |         | 1.5           | 85  | 76  | 70  | 65   | 83  | 75  | 69 | 64   | 80  | 73 | 68 | 63   | 77 | 71 | 66 | 63  | 60 |
|        |         |         | 2.0           | 90  | 83  | 78  | 73   | 88  | 82  | 77 | 72   | 85  | 80 | 75 | 71   | 82 | 77 | 74 | 70  | 67 |
| 取付高さ   | 器具間隔最大限 |         | 2.5           | 93  | 88  | 83  | 78   | 92  | 86  | 82 | 78   | 88  | 84 | 80 | 76   | 85 | 82 | 78 | 75  | 72 |
|        | 横方向 (A) | 縦方向 (B) | 3.0           | 96  | 91  | 86  | 82   | 94  | 89  | 85 | 82   | 91  | 87 | 83 | 80   | 88 | 84 | 81 | 79  | 76 |
| 1.5m   | 1.9m    | 2.13m   | 4.0           | 99  | 95  | 91  | 88   | 97  | 93  | 90 | 87   | 94  | 91 | 88 | 85   | 91 | 88 | 86 | 84  | 81 |
| 2      | 2.52    | 2.69    | 5.0           | 100 | 97  | 94  | 91   | 99  | 96  | 93 | 90   | 96  | 93 | 91 | 89   | 93 | 91 | 89 | 87  | 84 |
| 2.5    | 3.14    | 3.28    | 7.0           | 102 | 100 | 98  | 96   | 101 | 99  | 96 | 94   | 98  | 96 | 94 | 92   | 95 | 93 | 92 | 90  | 87 |
| 3      | 3.75    | 3.88    | 10.0          | 104 | 102 | 101 | 99   | 103 | 101 | 99 | 98   | 100 | 98 | 97 | 96   | 97 | 96 | 94 | 93  | 90 |

