

屋内照明器具特性

品番 (品名)	XND0639SW									
光源	LED4000_85_600 x1					600.0 l m				
管理番号	K0176073 (0) DB 1									
BZ分類	BZ1									

器具効率	100 %	天井	80 %				70 %				50 %				30 %				0 %																					
	上方光束		0 %	反射率	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %																			
	下方光束		100 %		床	10 %				10 %				10 %				10 %				0 %																		
室指数	照明率 (X0.01)																			ZCM																				
保守率	良	0.81	0.6	73	65	60	56	73	65	60	56	71	64	59	56	69	63	59	56	54																				
	中	0.77	0.8	83	75	70	67	82	75	70	67	80	74	70	66	78	73	69	66	65																				
	否	0.68	1.0	88	82	77	74	87	81	77	74	85	80	76	73	83	79	75	73	71																				
			1.25	92	87	83	80	91	86	82	79	89	85	82	79	87	84	81	78	77																				
下方投影面積			c m ²		1.5		95		90		86		83		94		90		86		83		92		88		85		82		90		87		84		82		80	
等価発光面積			c m ²		2.0		99		95		91		89		97		94		91		88		95		92		90		88		93		91		89		87		85	
取付高さ	器具間隔最大限		2.5		101		97		95		92		100		97		94		92		97		95		93		91		95		93		91		90		88			
	横方向 (A)	縦方向 (B)	3.0		102		99		97		95		101		98		96		94		99		96		95		93		97		95		93		92		90			
H m	1.09 H m	1.09 H m	4.0		104		101		99		98		102		100		99		97		100		99		97		96		98		97		96		94		92			
			5.0		105		103		101		100		103		102		100		99		101		100		99		97		99		98		97		96		94			
			7.0		106		104		102		101		105		103		102		101		101		100		99		100		99		99		98		96		95			
			10.0		107		106		105		104		105		104		104		103		103		102		101		101		100		100		99		97		97			

