

# 屋内照明器具特性

|         |                             |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
|---------|-----------------------------|--|--|--|--|--|--|--|--|--|--|--|--|--|--|
| 品番 (品名) | XLX410DEV T                 |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
| 光源      | LED3500_85_1900 x1 1900.0lm |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
| 管理番号    | K0130919(8)DB1              |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
| BZ分類    | BZ5                         |  |  |  |  |  |  |  |  |  |  |  |  |  |  |

|        |             |         |      |                 |      |     |     |      |     |     |     |     |     |     |     |     |     |     |     |     |
|--------|-------------|---------|------|-----------------|------|-----|-----|------|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|
| 器具効率   | 100%        | 天井      | 80%  |                 |      |     | 70% |      |     |     | 50% |     |     |     | 30% |     |     |     | 0%  |     |
|        |             |         | 壁    | 70              | 50   | 30  | 10  | 70   | 50  | 30  | 10  | 70  | 50  | 30  | 10  | 70  | 50  | 30  | 10  | 0%  |
| 上方光束   | 4%          | 反射率     | 床    | 10%             |      |     |     | 10%  |     |     |     | 10% |     |     |     | 10% |     |     |     | 0%  |
| 下方光束   | 96%         |         | 室指数  | 照明率 (X0.01) ZCM |      |     |     |      |     |     |     |     |     |     |     |     |     |     |     |     |
| 保守率    | 良<br>中<br>否 | 0.83    | 0.6  | 5.5             | 4.2  | 3.4 | 2.9 | 5.3  | 4.2 | 3.4 | 2.9 | 5.1 | 4.0 | 3.3 | 2.8 | 4.8 | 3.9 | 3.3 | 2.8 | 2.6 |
|        |             | 0.81    | 0.8  | 6.5             | 5.3  | 4.5 | 3.9 | 6.3  | 5.2 | 4.4 | 3.8 | 6.0 | 5.0 | 4.3 | 3.8 | 5.7 | 4.8 | 4.2 | 3.7 | 3.5 |
|        |             | 0.77    | 1.0  | 7.1             | 6.0  | 5.2 | 4.6 | 6.9  | 5.9 | 5.1 | 4.6 | 6.6 | 5.7 | 5.0 | 4.5 | 6.2 | 5.5 | 4.9 | 4.4 | 4.2 |
|        |             |         | 1.25 | 7.7             | 6.7  | 5.9 | 5.3 | 7.5  | 6.6 | 5.8 | 5.3 | 7.1 | 6.3 | 5.7 | 5.2 | 6.8 | 6.1 | 5.6 | 5.1 | 4.8 |
| 下方投影面積 |             |         | 1.5  | 8.1             | 7.2  | 6.5 | 5.9 | 7.9  | 7.0 | 6.4 | 5.8 | 7.5 | 6.8 | 6.2 | 5.7 | 7.2 | 6.6 | 6.0 | 5.6 | 5.3 |
| 等価発光面積 |             |         | 2.0  | 8.7             | 7.9  | 7.2 | 6.7 | 8.5  | 7.7 | 7.1 | 6.6 | 8.1 | 7.5 | 6.9 | 6.5 | 7.7 | 7.2 | 6.8 | 6.4 | 6.0 |
| 取付高さ   | 器具間隔最大限     |         | 2.5  | 9.0             | 8.4  | 7.8 | 7.3 | 8.8  | 8.2 | 7.7 | 7.2 | 8.5 | 7.9 | 7.4 | 7.0 | 8.1 | 7.6 | 7.2 | 6.9 | 6.6 |
|        | 横方向 (A)     | 縦方向 (B) | 3.0  | 9.3             | 8.7  | 8.2 | 7.7 | 9.1  | 8.5 | 8.0 | 7.6 | 8.7 | 8.2 | 7.8 | 7.5 | 8.4 | 8.0 | 7.6 | 7.3 | 6.9 |
| 1.5m   | 1.99m       | 2.17m   | 4.0  | 9.6             | 9.1  | 8.7 | 8.3 | 9.4  | 9.0 | 8.6 | 8.2 | 9.1 | 8.7 | 8.3 | 8.0 | 8.7 | 8.4 | 8.1 | 7.8 | 7.5 |
| 2      | 2.62        | 2.74    | 5.0  | 9.8             | 9.4  | 9.0 | 8.7 | 9.6  | 9.3 | 8.9 | 8.6 | 9.3 | 8.9 | 8.6 | 8.4 | 8.9 | 8.7 | 8.4 | 8.2 | 7.8 |
| 2.5    | 3.26        | 3.32    | 7.0  | 10.1            | 9.7  | 9.5 | 9.2 | 9.9  | 9.6 | 9.3 | 9.1 | 9.5 | 9.3 | 9.0 | 8.8 | 9.2 | 9.0 | 8.8 | 8.6 | 8.2 |
| 3      | 3.89        | 3.92    | 10.0 | 10.2            | 10.0 | 9.8 | 9.6 | 10.1 | 9.9 | 9.6 | 9.5 | 9.7 | 9.5 | 9.4 | 9.2 | 9.4 | 9.2 | 9.1 | 9.0 | 8.6 |

