

# 屋内照明器具特性

品番(品名)	NND26220Z	
光源	NND26220Z(GREEN) x1 370.0lm	
管理番号	K0128726(2)DB1	
BZ分類	BZ1	

器具効率	100%	天井	80%				70%				50%				30%				0%	
	上方光束 0%		反射率	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
下方光束	100%	床	10%				10%				10%				10%				0%	
室指数	照明率 ( X0.01 )																			ZCM
保守率	良 0.45	0.6	1.00	0.98	0.97	0.96	1.00	0.98	0.97	0.96	0.99	0.98	0.96	0.96	0.99	0.97	0.96	0.95	0.95	
	中 0.43	0.8	1.02	1.00	0.99	0.98	1.02	1.00	0.99	0.98	1.01	1.00	0.98	0.98	1.00	0.99	0.98	0.97	0.97	
	否 0.4	1.0	1.04	1.02	1.01	1.00	1.03	1.01	1.00	0.99	1.02	1.01	1.00	0.99	1.01	1.00	0.99	0.99	0.98	
下方投影面積	cm <sup>2</sup>	1.25	1.05	1.03	1.02	1.01	1.04	1.03	1.02	1.01	1.03	1.02	1.01	1.00	1.01	1.00	1.00	0.99	0.99	
		1.5	1.05	1.04	1.03	1.02	1.05	1.03	1.02	1.01	1.03	1.02	1.01	1.00	1.01	1.00	1.00	0.99	0.99	
等価発光面積	cm <sup>2</sup>	2.0	1.06	1.05	1.04	1.04	1.06	1.05	1.04	1.03	1.04	1.03	1.03	1.02	1.03	1.02	1.02	1.01	1.00	
		2.5	1.07	1.06	1.05	1.05	1.06	1.05	1.05	1.04	1.05	1.04	1.03	1.03	1.03	1.03	1.03	1.02	1.01	
取付高さ	器具間隔最大限		3.0	1.07	1.07	1.06	1.05	1.06	1.06	1.05	1.05	1.04	1.04	1.04	1.03	1.03	1.03	1.02	1.01	
	Hm	0.28Hm	0.28Hm	4.0	1.08	1.07	1.07	1.07	1.07	1.06	1.06	1.06	1.05	1.05	1.05	1.04	1.04	1.03	1.01	
			5.0	1.08	1.08	1.07	1.07	1.07	1.07	1.06	1.05	1.05	1.05	1.05	1.04	1.04	1.03	1.01	1.01	
			7.0	1.08	1.08	1.08	1.08	1.07	1.07	1.07	1.07	1.06	1.06	1.06	1.06	1.04	1.04	1.04	1.02	
			10.0	1.09	1.09	1.09	1.09	1.08	1.08	1.08	1.08	1.06	1.06	1.06	1.06	1.04	1.04	1.04	1.02	

