

屋内照明器具特性

品番 (品名)	NND2 6 2 5 0 Z		
光源	NND2 6 2 5 0 Z (BLUE) ×1 130.0 lm		
管理番号	K0129167 (2) DB 1		
BZ分類	BZ1		

器具効率	100%	天井	80%				70%				50%				30%				0%	
	上方光束 0%		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
下方光束	100%	床		10%				10%				10%				10%				0%
室指数	照明率 (X0.01)																			ZCM
保守率	良 0.45	0.6	92	88	85	84	92	88	85	84	91	87	85	83	90	87	85	83	82	
	中 0.43		0.8	96	92	90	88	95	92	90	88	94	91	89	88	93	91	89	87	86
	否 0.4		1.0	98	95	93	91	98	95	92	91	96	94	92	90	95	93	91	90	89
下方投影面積 等価発光面積	cm ²	1.25	100	97	95	93	100	97	95	93	98	96	94	93	97	95	93	92	91	
		1.5	102	99	97	95	101	98	97	95	99	97	96	94	98	96	95	94	92	
		2.0	103	101	99	98	102	100	99	97	101	99	98	97	99	98	97	96	94	
取付高さ	器具間隔最大限		2.5	104	102	101	100	103	102	100	99	102	100	99	98	100	99	98	97	95
	横方向 (A)	縦方向 (B)	3.0	105	103	102	101	104	103	101	100	102	101	100	99	100	99	99	98	96
1.5m	0.43m	0.5m	4.0	106	105	103	102	105	104	103	102	103	102	101	100	101	100	100	99	97
2	0.55	0.58	5.0	106	105	104	103	105	104	104	103	103	103	102	101	101	101	100	100	97
2.5	0.68	0.72	7.0	107	106	105	105	106	105	105	104	104	103	103	102	102	101	101	101	98
3	0.82	0.87	10.0	107	107	106	106	106	106	105	105	104	104	103	103	102	102	101	101	99

