

# 屋内照明器具特性

品番 (品名)	LGB16737	
光源	LLD4000LCB1 ×1	845.0 1 m
管理番号	K0176230(0)DR1	
BZ分類	BZ5	

器具効率	47%	天井	80%				70%				50%				30%				0%		
	上方光束		2%	反射率	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
	下方光束		45%		床	10%				10%				10%				10%			
室指数	照明率 ( X0.01 )																				ZCM
保守率	良	0.67	0.6	2.7	2.1	1.8	1.5	2.6	2.1	1.7	1.5	2.5	2.0	1.7	1.5	2.4	2.0	1.7	1.5	1.4	
	中	0.63	0.8	3.1	2.6	2.2	2.0	3.1	2.6	2.2	2.0	2.9	2.5	2.2	1.9	2.8	2.4	2.1	1.9	1.8	
	否	0.56	1.0	3.5	3.0	2.6	2.3	3.4	2.9	2.6	2.3	3.2	2.8	2.5	2.3	3.1	2.7	2.5	2.2	2.1	
			1.25	3.7	3.3	2.9	2.7	3.6	3.2	2.9	2.6	3.5	3.1	2.8	2.6	3.3	3.0	2.8	2.6	2.4	
下方投影面積	c m <sup>2</sup>		1.5	3.9	3.5	3.2	2.9	3.8	3.4	3.1	2.9	3.7	3.3	3.1	2.9	3.5	3.2	3.0	2.8	2.7	
	等価発光面積		c m <sup>2</sup>	2.0	4.2	3.8	3.5	3.3	4.1	3.8	3.5	3.3	3.9	3.6	3.4	3.2	3.7	3.5	3.3	3.2	3.0
取付高さ	器具間隔最大限		2.5	4.3	4.0	3.8	3.6	4.2	4.0	3.7	3.5	4.1	3.8	3.6	3.5	3.9	3.7	3.6	3.4	3.2	
	横方向 (A)	縦方向 (B)	3.0	4.5	4.2	4.0	3.8	4.4	4.1	3.9	3.7	4.2	4.0	3.8	3.7	4.0	3.9	3.7	3.6	3.4	
H m	0.82 H m	0.82 H m	4.0	4.6	4.4	4.2	4.0	4.5	4.3	4.2	4.0	4.3	4.2	4.0	3.9	4.2	4.1	3.9	3.8	3.7	
			5.0	4.7	4.5	4.4	4.2	4.6	4.4	4.3	4.2	4.4	4.3	4.2	4.1	4.3	4.2	4.1	4.0	3.8	
			7.0	4.8	4.7	4.5	4.4	4.7	4.6	4.5	4.4	4.5	4.4	4.4	4.3	4.4	4.3	4.2	4.2	4.0	
			10.0	4.9	4.8	4.7	4.6	4.8	4.7	4.6	4.5	4.6	4.6	4.5	4.4	4.5	4.4	4.4	4.3	4.1	

