

屋内照明器具特性

品番 (品名)	LGBC55010									
光源	LED5000_70_797 x1					797.0 lm				
管理番号	K0172991(0)DR1									
BZ分類	BZ5									

器具効率	100%	天井	80%				70%				50%				30%				0%	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%	
上方光束	1%	床	10%				10%				10%				10%				0%	
下方光束	99%	室指数	照明率 (X0.01)																ZCM	
保守率	良	0.67	0.6	57	45	38	32	56	45	37	32	54	44	37	32	51	42	36	32	30
	中	0.63	0.8	67	56	48	43	66	55	48	42	63	54	47	42	60	52	46	42	40
	否	0.56	1.0	74	63	56	50	72	62	55	50	69	61	54	49	66	59	53	49	47
			1.25	80	70	63	57	78	69	62	57	75	67	61	56	72	65	60	56	54
下方投影面積	cm ²		1.5	84	75	68	63	82	74	68	62	79	72	66	62	76	70	65	61	59
等価発光面積	cm ²		2.0	89	82	76	71	88	81	75	70	84	79	74	70	81	76	72	69	66
取付高さ	器具間隔最大限		2.5	93	86	81	76	91	85	80	76	88	83	79	75	85	81	77	74	71
	横方向 (A)	縦方向 (B)	3.0	95	90	85	81	93	88	84	80	90	86	82	79	87	84	81	78	75
Hm	1.21Hm	1.21Hm	4.0	98	94	90	86	97	92	89	86	94	90	87	84	91	88	85	83	80
			5.0	100	96	93	90	98	95	92	89	96	93	90	88	93	90	88	86	83
			7.0	102	99	97	94	101	98	96	94	98	96	94	92	95	93	92	90	87
			10.0	104	102	100	98	102	101	99	97	100	98	97	95	97	96	95	93	90

