

屋内照明器具特性	
品番 (品名)	LGB51200
光源	LED5000_70_538 x1 538.0 l m
管理番号	K0154735(0)DB1
BZ分類	BZ6/0.7/BZ5

器具効率	100%	天井	80%				70%				50%				30%				0%	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%	
上方光束	16%	床	10%				10%				10%				10%				0%	
下方光束	84%	室指数	照明率 ( X0.01 )																ZCM	
保守率	良	0.69	0.6	53	40	32	27	51	39	32	27	47	37	30	26	43	35	29	25	22
	中	0.67	0.8	62	50	42	36	60	49	41	36	55	46	39	34	51	43	38	33	30
	否	0.63	1.0	68	57	49	43	66	56	48	43	61	52	46	41	56	49	44	39	35
			1.25	74	64	56	50	71	62	55	49	66	58	52	47	61	55	50	46	41
下方投影面積			1.5	78	69	62	56	75	67	60	55	70	63	57	52	65	59	54	50	46
			2.0	84	76	70	64	81	74	68	63	75	69	64	60	70	65	61	57	52
取付高さ	器具間隔最大限		2.5	88	81	75	70	85	78	73	68	79	74	69	65	73	69	66	62	57
	横方向 (A)	縦方向 (B)	3.0	90	84	79	74	87	81	77	72	81	77	73	69	76	72	69	66	60
Hm	1.35Hm	1.23Hm	4.0	93	88	84	80	90	86	82	78	85	81	78	74	79	76	73	71	65
			5.0	95	91	87	84	92	89	85	82	87	84	81	78	81	79	76	74	68
			7.0	98	95	92	89	95	92	89	87	89	87	84	82	84	82	80	78	72
			10.0	100	97	95	93	97	94	92	91	91	89	88	86	86	84	83	82	75

