

# 屋内照明器具特性

|         |                              |  |  |  |  |  |  |  |  |  |
|---------|------------------------------|--|--|--|--|--|--|--|--|--|
| 品番 (品名) | LGB51371                     |  |  |  |  |  |  |  |  |  |
| 光源      | LED3500_70_2080 x1 2080.0 1m |  |  |  |  |  |  |  |  |  |
| 管理番号    | K0154730(0)DB1               |  |  |  |  |  |  |  |  |  |
| BZ分類    | BZ6/0.7/BZ5                  |  |  |  |  |  |  |  |  |  |

|        |               |         |      |      |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |
|--------|---------------|---------|------|------|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|
| 器具効率   | 100%          | 天井      | 80%  |      |     |     | 70% |     |     |     | 50% |     |     |     | 30% |     |     |     | 0%  |     |     |
|        | 上方光束          |         | 17%  | 反射率  | 70  | 50  | 30  | 10  | 70  | 50  | 30  | 10  | 70  | 50  | 30  | 10  | 70  | 50  | 30  | 10  | 0%  |
|        | 下方光束          |         | 83%  |      | 床   | 10% |     |     |     | 10% |     |     |     | 10% |     |     |     | 10% |     |     |     |
| 室指数    | 照明率 ( X0.01 ) |         |      |      |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     | ZCM |     |
| 保守率    | 良             | 0.69    | 0.6  | 5.2  | 4.0 | 3.2 | 2.7 | 5.0 | 3.9 | 3.1 | 2.6 | 4.6 | 3.6 | 3.0 | 2.5 | 4.3 | 3.4 | 2.8 | 2.4 | 2.1 |     |
|        | 中             | 0.67    | 0.8  | 6.2  | 5.0 | 4.2 | 3.6 | 5.9 | 4.8 | 4.1 | 3.5 | 5.5 | 4.5 | 3.9 | 3.4 | 5.0 | 4.3 | 3.7 | 3.2 | 2.9 |     |
|        | 否             | 0.63    | 1.0  | 6.8  | 5.7 | 4.9 | 4.3 | 6.5 | 5.5 | 4.8 | 4.2 | 6.0 | 5.2 | 4.5 | 4.0 | 5.6 | 4.8 | 4.3 | 3.9 | 3.4 |     |
|        |               |         | 0.63 | 1.25 | 7.4 | 6.4 | 5.6 | 5.0 | 7.1 | 6.2 | 5.5 | 4.9 | 6.6 | 5.8 | 5.2 | 4.7 | 6.1 | 5.4 | 4.9 | 4.5 | 4.0 |
| 下方投影面積 |               |         | 1.5  | 7.8  | 6.9 | 6.1 | 5.6 | 7.5 | 6.7 | 6.0 | 5.4 | 6.9 | 6.2 | 5.7 | 5.2 | 6.4 | 5.8 | 5.3 | 4.9 | 4.4 |     |
|        | 等価発光面積        |         | 2.0  | 8.4  | 7.6 | 6.9 | 6.4 | 8.1 | 7.3 | 6.7 | 6.2 | 7.5 | 6.9 | 6.4 | 5.9 | 6.9 | 6.4 | 6.0 | 5.6 | 5.1 |     |
| 取付高さ   | 器具間隔最大限       |         | 2.5  | 8.7  | 8.0 | 7.5 | 6.9 | 8.4 | 7.8 | 7.2 | 6.8 | 7.8 | 7.3 | 6.8 | 6.4 | 7.3 | 6.8 | 6.5 | 6.1 | 5.5 |     |
|        | 横方向 (A)       | 縦方向 (B) | 3.0  | 9.0  | 8.4 | 7.8 | 7.4 | 8.7 | 8.1 | 7.6 | 7.2 | 8.1 | 7.6 | 7.2 | 6.8 | 7.5 | 7.1 | 6.8 | 6.5 | 5.9 |     |
| 1.5m   | 2.08m         | 2.09m   | 4.0  | 9.3  | 8.8 | 8.4 | 8.0 | 9.0 | 8.5 | 8.1 | 7.8 | 8.4 | 8.0 | 7.7 | 7.4 | 7.8 | 7.5 | 7.2 | 7.0 | 6.3 |     |
| 2      | 2.75          | 2.64    | 5.0  | 9.5  | 9.1 | 8.7 | 8.4 | 9.2 | 8.8 | 8.5 | 8.2 | 8.6 | 8.3 | 8.0 | 7.7 | 8.0 | 7.8 | 7.5 | 7.3 | 6.6 |     |
| 2.5    | 3.42          | 3.22    | 7.0  | 9.8  | 9.4 | 9.1 | 8.9 | 9.5 | 9.2 | 8.9 | 8.6 | 8.8 | 8.6 | 8.4 | 8.2 | 8.3 | 8.1 | 7.9 | 7.7 | 7.0 |     |
| 3      | 4.08          | 3.81    | 10.0 | 10.0 | 9.7 | 9.5 | 9.3 | 9.6 | 9.4 | 9.2 | 9.0 | 9.0 | 8.9 | 8.7 | 8.5 | 8.5 | 8.3 | 8.2 | 8.1 | 7.3 |     |

