

# 屋内照明器具特性

品番 (品名)	NNF 5 1 2 1 0															
光源	LED5000_85_4600 x1 4600.0 1 m															
管理番号	K0172825 ( 0 ) DR 1															
BZ分類	BZ6															

器具効率	100 %	天井	80 %				70 %				50 %				30 %				0 %		
			反射率	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
上方光束 下方光束	20 % 80 %	室指数	照明率 ( X0.01 ) ZCM																		
保守率	良 中 否 0.83 0.81 0.77	0.6	51	39	31	25	49	37	30	25	44	35	28	23	40	32	26	22	19		
		0.8	60	48	40	34	58	47	39	33	53	43	37	32	48	40	34	30	26		
		1.0	67	55	47	41	64	53	46	40	58	49	43	38	53	46	40	36	31		
		1.25	73	62	54	48	69	60	52	47	63	55	49	44	58	51	46	42	37		
下方投影面積 等価発光面積	c m <sup>2</sup> c m <sup>2</sup>	1.5	77	67	59	53	73	64	58	52	67	60	54	49	61	55	50	46	41		
		2.0	82	74	67	62	79	71	65	60	72	66	61	56	66	61	57	53	47		
取付 高さ	器具間隔最大		2.5	86	79	73	67	82	76	70	65	76	70	66	62	69	65	61	58	51	
	横方向 (A)	縦方向 (B)	3.0	89	82	77	72	85	79	74	70	78	73	69	65	72	68	65	61	55	
1.5m	2.22 m	2.09 m	4.0	92	87	82	78	88	84	79	75	82	78	74	71	75	72	69	66	59	
2	2.93	2.63	5.0	94	90	85	82	90	86	83	79	84	80	77	74	77	75	72	70	62	
2.5	3.64	3.19	7.0	96	93	90	87	93	90	87	84	86	84	81	79	80	78	76	74	66	
3	4.34	3.77	10.0	98	96	93	91	95	93	90	88	88	86	84	83	82	80	79	77	69	

