

屋内照明器具特性	
品番 (品名)	L G W 5 0 6 3 0 F
光源	LDA7N- G/ E/ W ×2 810.0 l m
管理番号	K0169055 (0) DB 1
B Z 分類	B Z 6

器具効率	63 %	天井	80 %				70 %				50 %				30 %				0 %	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
上方光束	10 %	床	10 %				10 %				10 %				10 %				0 %	
下方光束	53 %	室指数	照明率 (X0.01)																Z C M	
保守率	良 中 否 0.63 0.6 0.56	0.6	32	24	19	15	30	23	18	15	28	22	17	14	26	20	16	14	12	
		0.8	38	30	24	21	36	29	24	20	33	27	23	19	30	25	21	18	16	
		1.0	42	34	29	25	40	33	28	24	37	31	26	23	34	29	25	22	19	
		1.25	45	38	33	29	43	37	32	28	40	34	30	27	37	32	29	26	23	
下方投影面積	c m ²	1.5	48	41	36	32	46	40	35	32	42	37	33	30	39	35	31	29	25	
		2.0	51	46	41	37	49	44	40	37	46	41	38	35	42	39	36	33	30	
取付高さ	器具間隔最大限		2.5	54	49	45	41	52	47	43	40	48	44	41	38	44	41	39	36	32
	横方向 (A)	縦方向 (B)	3.0	55	51	47	44	53	49	46	43	49	46	43	41	46	43	41	39	35
H m	1.33 H m	1.33 H m	4.0	58	54	51	48	56	52	49	47	52	49	46	44	48	46	44	42	38
			5.0	59	56	53	50	57	54	52	49	53	51	49	47	49	48	46	44	40
			7.0	61	58	56	54	59	56	54	52	55	53	51	50	51	50	48	47	43
			10.0	62	60	58	57	60	58	57	55	56	55	54	52	53	52	51	49	45

