

屋内照明器具特性	
品番 (品名)	NNFS41038J
光源	LDL40S.N/14/26 x1 2600.0 lm
管理番号	K0133637(7)DB1
BZ分類	BZ6

器具効率	97%	天井	80%				70%				50%				30%				0%				
			壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%			
上方光束	20%	反射率	10%				10%				10%				10%				0%				
下方光束	77%		床	10%				10%				10%				10%				0%			
室指数			照明率 (X0.01)																				ZCM
保守率	良 中 否 0.83 0.81 0.77	0.6	49	36	28	23	46	35	27	22	42	32	26	21	38	30	24	20	16				
		0.8	57	45	37	31	55	44	36	30	49	40	34	29	45	37	31	27	23				
		1.0	64	52	44	38	60	50	42	36	55	46	39	34	49	42	37	32	28				
		1.25	69	58	50	44	66	56	49	43	60	52	45	40	54	47	42	38	33				
下方投影面積	c m ²	1.5	73	63	55	49	70	61	53	48	63	56	50	45	57	51	46	42	36				
		2.0	79	70	63	57	75	67	61	55	68	62	57	52	62	57	52	49	42				
取付高さ	器具間隔最大限		2.5	82	75	68	63	79	72	66	61	72	66	61	57	65	61	57	53	46			
	横方向 (A)	縦方向 (B)	3.0	85	78	72	67	81	75	70	65	74	69	65	61	68	64	60	57	50			
1.5m	2.21m	2.13m	4.0	88	83	78	73	85	79	75	71	78	73	70	66	71	68	65	62	54			
2	2.91	2.69	5.0	90	86	81	77	87	82	78	75	80	76	73	70	73	70	68	65	58			
2.5	3.62	3.26	7.0	93	89	86	82	89	86	83	80	82	80	77	75	76	74	72	69	62			
3	4.32	3.86	10.0	95	92	89	87	91	89	86	84	85	82	80	79	78	76	75	73	65			

